HEX31WP-TX


HDMI Wall Plate HDBaseT™ Transmitter

Description

Our HEX31WP HDMI/USB-C wall plate HDBaseT™ transmitter is a multi-format 4K input switcher solution delivering HDMI and USB-C inputs up to 70m 1080p (40m 4K). The HEX31WP-TX features both manual or automated source selection and includes display on / off control via CEC, RS-232 and IR (via compatible HDBaseT™ receivers). The HEX31WP-TX has been designed to work with all Blustream HDBaseT™ receiver solutions, be installed in both UK and European backboxes and can be powered locally or from compatible Blustream HDBaseT[™] products.


Specifications

- Video Input Connectors: 2 x HDMI Type A, 19-pin, female, 1 x USB-C Type C
- Video Output Connectors: 1 x HDBaseT™ RJ45 connector
- RS-232 serial port: 1 x 3-Pin Phoenix connector
- IR Input port: 1 x 3-Pin Phoenix connector
- Product upgrade: 1 x Micro USB female
- Local power input: 1 x 2-Pin Phoenix connector
- Casing Dimensions (W x H x D): 146mm x 86mm x 44mm
- Operating Temperature: 32°F to 104°F (-5°C to +55°C)
- Storage Temperature: -4°F to 140°F (-25°C to +70°C)
- Power Supply: 12V/1A DC





- Features 2 x HDMI & 1 x USB-C inputs with manual / auto source selection
- Advanced HDBaseT[™] technology offering distribution of video and audio over a single CAT cable
- Supports 4K UHD video up to 40m (3840 x 2160 @30Hz 4:4:4, 4096 x 2160 @24Hz 4:4:4, and 4K @60Hz 4:2:0)
- Extends HDMI 1080p up to a distance of 70m
- Supports all known HDMI audio formats including Dolby TrueHD, Dolby Atmos, Dolby Digital Plus and DTS-HD Master Audio transmission
- Input selection via front panel, IR and RS-232
- Programmable ON / OFF button utilising IR, RS-232 or CEC for control of display device at HDBaseT™ Receiver
- Supports 12V-48V PoC from compatible Blustream HDBaseT™ Matrix
- Bi-directional RS-232 pass through
- Supports IR pass-through to HDBaseT™ Matrix or Receiver
- Compatible with all Blustream HDBaseT™ Matrix or Receivers*
- Magnetic faceplate surround allowing both UK & EU backbox compatibility
- HDCP 2.2 support
- *Technical performance is subject to the features supported on the connected HDBaseT[™] product
- ** Please note: The USB-C input port on this unit does not provide PD charging to devices connected for video distribution.























Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.







