

New Product Summary

Launch Date – October 2009

EPSON

EB-1723

The EB-1723 will offer you two highly valuable features you need for any on the go presentations. You'll be able to project in almost any meeting room conditions thanks to its high colour light output of 2'700 lumens, packed in an astonishing 1.8kg compact body. It guarantees that you will have a great picture quality and colours at any time.

We've added a short throw lens in order to get a bigger picture from a shorter distance, enhancing your impact while presenting!

Perfectly projected images wherever you are

When you are on the move can you be sure the conditions will be right for your presentation? With the Epson EB-1723, clear and natural images are guaranteed in the lightest room, thanks to the innovative Epson E-TORL lamp technology which provides a Colour Light Output of 2700 lumens.

Optional Wireless Connectivity

The Epson EB-1723 can be made even more versatile with the optional wireless connectivity. Purchase the optional wireless module and connect wirelessly to your network and benefit from the most secure 802.11a/b/g wireless LAN transmission.

A truly mobile solution

Weighing as little as 1.8kg and supplied with a compact, stylish carrying case this 3LCD projector is the perfect travel companion.

Ready in seconds – simply plug and project

All that is needed to set up your projector is to plug it in, connect your source and within seconds you are ready to present. The projected image is instantly aligned thanks to automatic vertical keystone correction, and the projection level can be easily adjusted using the single foot release lever. When you have finished your presentation, simply switch off and pack away. With the instant off button there's no waiting around for the projector to cool down.

Smart & Friendly Design

- Bright images with 2700 lumens from an energy efficient, Epson exclusive E-TORL lamp
- No time wasting - with quick startup, automatic vertical keystone correction and quick cool down
- 60" image from only 1.3 metres - clear presentations in almost any room
- AV mute slide - for more effective presentations
- Exceptional image quality through Epson's 3LCD technology
- Monitor and control through direct network connection via the optional Ethernet or wireless modules
- 3 in 1 USB Display for enhanced ease of use
- Internal 1W speaker for added audio capabilities
- Optional Wireless Connection

*in low brightness mode



EPSON
WORLD LEADER
IN PROJECTORS

E-TORL 3LCD



2700 lm



1.8 kg



1 W



XGA



2-in-1
USB display



WiFi
Ethernet

Ordering Information

| | |
|-------------------|-------------------------------|
| Description | EB-1723 - XGA, 3LCD Projector |
| Part Number | EB-1723 - V11H268C40 |
| EAN Codes | EB-1723 – 8715946456959 |
| Carton Dimensions | TBC (D x W x H) |
| Carton Weight | TBC |

- The last two letters may vary depending on the version. See the RRP list or Trade Price lists for correct part codes.

Screen Size & Projection Distance

Use the Epson Projection Distance Calculator software available from www.epson.co.uk for distances and screen sizes not shown below.

4 : 3

| Screen size [inch] | Projection distance | | | | | |
|-----------------------|---------------------|------|------|------|------|------|
| | Wide | | | Tele | | |
| | cm | inch | foot | cm | inch | foot |
| 30 | 65 | 26 | 2.1 | 80 | 32 | 2.6 |
| 40 | 88 | 35 | 2.9 | 108 | 42 | 3.5 |
| 50 | 111 | 44 | 3.6 | 136 | 53 | 4.4 |
| 60 | 133 | 53 | 4.4 | 163 | 64 | 5.4 |
| 80 | 179 | 70 | 5.9 | 218 | 86 | 7.2 |
| 100 | 224 | 88 | 7.4 | 274 | 108 | 9 |
| 150 | 338 | 133 | 11.1 | 412 | 162 | 13.5 |
| 200 | 451 | 178 | 14.8 | 550 | 216 | 18 |
| 250 | 565 | 222 | 18.5 | 688 | 271 | 22.6 |
| 300 | 678 | 267 | 22.3 | 826 | 325 | 27.1 |

Accessories

(model code) **order code**

Consumables

Spare Lamp

V13H010L48 (ELPLP48)



Air Filter

V13H134A19 (ELPAF19)




Screens

80" Mobile Screen 16:9

V12H002S2Y (ELPSC21)

80" Pantograph Screen 16:10

V12H002S24 (ELPSC24)



Multi-Aspect Screen 65"/74"/80"

V13H003S26 (ELPSC26)

Mountings

Ceiling Plate

Required if using a ceiling pipe.

V12H003B23 (ELPMB23)



Pipe 450mm White

V12H003P13 (ELPFP13)



Pipe 700mm White

V12H003P14 (ELPFP14)



Cables

VGA Computer Cable HD-15 to HD-15 1.8m (ELPKC02)

V12H005C02

VGA Computer Cable HD-15 to HD-15 3.0m (ELPKC09)

V12H005C09

VGA Computer Cable HD-15 to HD-15 20m (ELPKC10)

V12H005C10



Component Video Cable

(ELPKC19)

V12H005C19



HD-TV Cable

(ELPKC22)

V12H005C22



Others

Wireless LAN Unit (ELPAP03)

V12H306P12



Ethernet Unit (ELPAP02B With LAN Unit Cover)

V12H005M0B



Quick Wireless Connection USB

Key (ELPAP05)

V12H005M05



Document Camera (ELP DC-06)



What's In The Box

Projector



Remote Control



2 x AAA Manganese Batteries
for the remote control



Power Cable

3 m cable



Computer Cable

Mini D-Sub 15-pin/mini D-Sub 15-pin, 1.8 m (6 ft.)



USB Cable

USB type A/USB type B, 1.8 m (6 ft.)



Audio Adapter

3.5 mm Stereo mini plug to RCA pin jack x 2 red/white, 15 cm.



Soft Case



User's Manual



Document & Software CD-ROM



Password Protect Sticker



Safety Instructions



PRODUCT SPECIFICATIONS

| | |
|---|---|
| PROJECTION TECHNOLOGY | 3LCD Technology (0.7" D7 Panels with MLA) |
| RESOLUTION | XGA – 1024 x 768 (4/3 aspect ratio) Up to UXGA (1600x1200) |
| WHITE LIGHT OUTPUT* (Brightness) (Normal/Eco) | 2700 – 1700 Lumens |
| COLOUR LIGHT OUTPUT (Normal/Eco) | 2700 – 1700 Lumens |
| CONTRAST | 2000:1 |
| IMAGE SIZE | 30" to 300" 60" screen: 1.33 – 1.63 m (projection distance) |
| LENS TYPE F-number: Focal Length: Offset: | 1.58-1.68 16.1mm – 19.3 mm 6:1 |
| ZOOM RATIO | Optical zoom x1.2 |
| NOISE LEVEL (Normal/Eco) | 39 dB / 30 dB |
| LAMP | 170 W UHE – E-TORL (ELP LP48) |
| SOUND | 1 x 1 watt |
| ADVANCED FEATURES | Security: padlock and security cable hole, kensington lock hole, password protection Operation: direct power on, quick start (5 secs.), instant off Display: 8 colours mode, e-zoom, A/V mute, source search, freeze |
| KEystone CORRECTION | Automatic, $\pm 30^\circ$ |
| INPUT Computer Video USB Network | 1 x D-sub 15-pin (RGB) 1 x RCA, 1 x S-Video 1 x USB 2.0 type B Optional RJ45 (ELPAP02B) |
| WIRELESS | Optional a/b/g (ELPAP03) |
| AUDIO | 1 x Stereo mini jack (RCA adapter provided) |
| CONTROL | Via optional LAN or WIRELESS |
| WEIGHT | 1.8 kg |
| DIMENSIONS (DxWxH) | 202 x 284 x 65 mm |
| LANGUAGE | English/Japanese/Chinese/Korean/German/French/Spanish/Italian/ Portuguese/Dutch/Swedish/Russian/Polish/Danish/Norwegian/Finnish/ Greek/Turkish/Czech/Hungarian/Arabic/Traditional Chinese/ Thailand/Romania/Slovenia/Ukrainian/Catalan |
| POWER CONSUMPTION | On: 230W Standby: 5.5W |
| SAFETY REGULATIONS | IEC 60950-1 1st edition (CE marking) EMC directive (89/336/EEC) Recycling regulations |
| WARRANTY | 3 years |

* ISO 21118 based measurement



3LCD E-TORL

For further information please visit www.epson.co.uk

Trademarks and registered trademarks are the property of Seiko Epson® Corporation or their respective owners.

Product information is subject to change without prior notice.