Launch Date: November 2009

NEW PRODUCT SUMMARY

EPSON EB-1925W

Ultra Bright and Portable

The EB-1925W offers superior 4000 lumens colour light output with portable weight. Thanks to its automatic functions, you can set up the projector anywhere and be ready in seconds. The EB-1925W is the perfect solution for stress-free mobile presentations.

With its rich features and connectivity, you can broaden your multimedia experience and impress the audience with smart and stylish presentations. Keep your lights on and dazzle your audience.

Advanced Auto Keystone Correction

This function automatically detects the projector's vertical angle and adjust the vertical keystone distortion instantly, ensuring that setup can be achieved quickly and efficiently allowing you to concentrate on your presentation.

Rich features and connectivity

With its rich features and connectivity, you can broaden your multimedia experience and impress the audience with smart and stylish presentations. No more hassle with cables. Directly connect your PC to the projector via a simple USB cable. Additional connectivity with HDMI.

4000 lm 3.4 kg USB display

ORDERING INFORMATION

Description	EB-1925W - WXGA, 3LCD Projector
Part Number	EB-1925W - V11H314070
Barcode	EB-1925W - 8715946458984
Carton Dimensions	522 x 390 x 230 mm (LxWxH)
Carton Gross Weight	6.69 kg

EPSON[®] EXCEED YOUR VISION

KEY SELLING POINTS

- Epson 3LCD technology offers perfect colour reproduction and bright natural pictures at 4000 lms in only 3.5 kg
- Automatic image adjust functions
- 3-in-1 USB display: sound, image, control
- Easy MP PC-Free: image/ presentation/ movie viewer from USB flash drive
- EasyMP Network Presentation: Wired or Wireless Connection from PC to projector
- Direct connection to Epson USB Document Camera (ELP-DC06)
- Rich connectivity with HDMI

TARGT MARKET

Corporate: installed on the ceiling, desktop usage, on the move (mobile presentation)

Content: PPT presentations, spreadsheets, (corporate) videos, advertisement, flash animations, websites









SCREEN SIZE & PROJECTION DISTANCE

Use the Epson Projection Distance Calculator software available from www.epson.co.uk for distances and screen sizes not shown below.

16:10						
Screen	Projection distance					
size		Wide			Tele	
(inch)	cm	inch	foot	cm	inch	Foot
28	91	36	3	150	59	4.9
30	123	48	4	201	79	6.6
40	155	61	5.1	253	100	8.3
50	187	74	6.1	305	120	10
60	251	99	8.2	408	161	13.4
80	315	124	10.3	511	201	16.8
100	476	187	15.6	769	303	25.2
150	636	250	20.9	1027	404	33.7
200	796	313	26.1	1285	506	42.1
250	956	376	31.4	1542	607	50.6
260	91	36	3	150	59	4.9

ACCESORIES

(model code) order code

Consumables	
Spare Lamp V13H010L53 (ELPLP53)	T
Air Filter V13H134A24 (ELPAF24)	\Diamond
Screens	
80" Mobile Screen 16:9 V12H002S21 (ELPSC21)	
80" Pantograph Screen 16:10	
V12H002S24 (ELPSC24)	
Multi-Aspect Screen 65"/74"/80"	<u> </u>
V13H003S26 (ELPSC26)	
Mountings	
Ceiling Plate Required if using a ceiling pipe. V12H003B23 (ELPMB23)	AL III
Pipe 450mm White V12H003P13 (ELPFP13)	~
Pipe 700mm White V12H003P14 (ELPFP14)	
Options	

USB Document Camera V12H321001 (ELPDC06)	1
Wireless LAN Unit V12H306P12 (ELPAP03)	
Quick Wireless Connection USB key V13H005M06 (ELPAP06)	_

Т

WHAT'S IN THE BOX

Projector	
Remote control	
2 x AA Manganese Batteries for the remote control	
Power Cable 3 m cable	<i>a</i>
Computer Cable Mini D-Sub 15-pin/mini D-Sub 15-pin, 1.8 m (6 ft.)	and the second s
USB Cable USB type A/USB type B, 3 m (6 ft.)	×
Soft Carrying Case	1000
Bundled Software	
User's Manual	Erector User's Culdes Materials Policity B = 56 B > 56
Document CD-ROM	
Password Protect Sticker	
Safety Instructions	



PRODUCT SPECIFICATIONS

PROJECTION TECHNOLOGY	21 CD Technology
RESOLUTION	3LCD Technology WXGA – 1280 x 800 (16/10 aspect ratio)
HEODEOHON	Up to 1080p
WHITE LIGHT OUTPUT *	
(Brightness) (Normal/Eco)	4000 – 2700 Lumens
COLOUR LIGHT OUTPUT	1000 0700 1
(Normal/Eco)	4000 – 2700 Lumens
CONTRAST	2000:1
IMAGE SIZE	30" to 300"
	60" screen: 1.87 – 3.05 m (projection distance)
LENS TYPE	
F-number:	1.75 – 2.42
Focal Length:	24.0 – 38.2 mm
Offset:	15.6:1
Throw Ratio:	1.45-2.33:1
	Optical zoom 1-1.6
NOISE LEVEL (Normal/Eco)	37 dB / 29 dB
Туре	230 W UHE – E-TORL (ELPLP53)
Life (Normal/Eco)	250 W OHE - E-TORL (ELPLP53) 2500hours / 3500hours
SOUND	1 x 10 watt
ADVANCED FEATURES	Security: Padlock and security cable hole, Kensington
	Lock, Password protection, Wireless LAN Unit Lock
	Operation: Screen Fit, Auto Focus, Direct Power On/Off,
	Quick start (10 secs.), Instant Off, Source search
	Display: 8 colour modes, Multi screen colour adjustment,
	E-zoom, A/V mute, Freeze
KEYSTONE CORRECTION	Automatic, Vertical ±30°
VISUAL INPUT	Automatic, Horizontal ±20°
Computer	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B
Video	1 x RCA, 1 x S-Video, 2 x Component (D-sub 15-pin)
USB flash drive	1 x USB 2.0 type A
Digital	1 x HDMI
USB Document Camera	1 x USB 2.0 type A
VISUAL OUTPUT	
Monitor	1 x D-sub 15-pin
AUDIO INPUT	
Computer	2 x Stereo mini-jack
Video	1 x RCA (White/Red)
Digital	
· · · · · ·	1 x HDMI
AUDIO OUTPUT	
AUDIO OUTPUT Computer	1 x Stereo mini-jack
AUDIO OUTPUT Computer WIRELESS CONNECTION	1 x Stereo mini-jack 1 x Wireless LAN unit
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45)
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch /
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish /
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch /
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak /
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak / Romanian / Croatian / Slovenian / Ukrainian / Catalan / Greek / Turkish / Arabic / Hebrew / Japanese / Simplified Chinese / Traditional Chinese / Korean / Thai /
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS LANGUAGE	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak / Romanian / Croatian / Slovenian / Ukrainian / Catalan / Greek / Turkish / Arabic / Hebrew / Japanese / Simplified Chinese / Traditional Chinese / Korean / Thai / Indonesian / Malay / Vietnamese
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak / Romanian / Croatian / Slovenian / Ukrainian / Catalan / Greek / Turkish / Arabic / Hebrew / Japanese / Simplified Chinese / Traditional Chinese / Korean / Thai / Indonesian / Malay / Vietnamese On: 237W (Eco)
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS LANGUAGE POWER CONSUMPTION	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak / Romanian / Croatian / Slovenian / Ukrainian / Catalan / Greek / Turkish / Arabic / Hebrew / Japanese / Simplified Chinese / Traditional Chinese / Korean / Thai / Indonesian / Malay / Vietnamese On: 237W (Eco) Standby: 0.3W (Eco)
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS LANGUAGE	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak / Romanian / Croatian / Slovenian / Ukrainian / Catalan / Greek / Turkish / Arabic / Hebrew / Japanese / Simplified Chinese / Traditional Chinese / Korean / Thai / Indonesian / Malay / Vietnamese On: 237W (Eco) Standby: 0.3W (Eco) IEC 60950-1 1st edition (CE marking)
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS LANGUAGE POWER CONSUMPTION	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak / Romanian / Croatian / Slovenian / Ukrainian / Catalan / Greek / Turkish / Arabic / Hebrew / Japanese / Simplified Chinese / Traditional Chinese / Korean / Thai / Indonesian / Malay / Vietnamese On: 237W (Eco) Standby: 0.3W (Eco) IEC 60950-1 1st edition (CE marking) EMC directive (89/336/EEC)
AUDIO OUTPUT Computer WIRELESS CONNECTION CONTROL WEIGHT DIMENSIONS LANGUAGE POWER CONSUMPTION	1 x Stereo mini-jack 1 x Wireless LAN unit 1 x RS-232C (D-sub 9-pin), 1 x LAN (RJ45) 3.5 kg 257 x 357 x 86 mm English / French / German / Italian / Spanish / Dutch / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Bulgarian / Polish / Hungarian / Czech / Slovak / Romanian / Croatian / Slovenian / Ukrainian / Catalan / Greek / Turkish / Arabic / Hebrew / Japanese / Simplified Chinese / Traditional Chinese / Korean / Thai / Indonesian / Malay / Vietnamese On: 237W (Eco) Standby: 0.3W (Eco) IEC 60950-1 1st edition (CE marking)

* ISO 21118 based measurement



For further information please contact your local Epson office or visit www.epson-europe.com

Trademarks and registered trademarks are the property of Seiko Epson[®] Corporation or their respective owners. Product information is subject to change without prior notice.

