EB-G6570WU

DATASHEET





















The EB-G6570WU is a professional installation projector ideal for corporate environments, education applications, rental markets and digital signage. Important presentations and sales campaigns are delivered with rich, vivid colours - even in daylight, thanks to Epson's 3LCD technology and equally high White and Colour Light Output. The projector can even be placed in difficult positions thanks to a number of innovative installation features.

Ensure superb quality and the best possible delivery of presentations with the EB-G6570WU. This 5,200-lumen projector includes Epson's 3LCD technology and high brightness to display images with more accurate colours and clearer detail. A new enhanced standard lens helps reduce flare and improve focus.

Set-up and installation is simple and straightforward. A wide lens shift allows easy placement of the projector, even in difficult positions, without distorting or blurring the image. In addition, a powerful zoom lens, as well as manual vertical keystone correction and centred lens, make it even easier to set-up in various positions. The projector can also be rotated vertically by 360 degrees allowing images to be projected directly onto the ceiling and the floor¹.



KEY FEATURES

- Ultra-bright output
 Equally high 5,200lm White and Colour
 Light Output
- High-quality image
 3LCD technology, WCLO, colour uniformity, enhanced standard lens
- Flexible installation
 Wide lens shift, manual vertical keystone correction
- Easy to set up HDBaseT and HDMI connectivity. Compatible with Epson EB-G5 series lenses²





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.76 inch with C2 Fine

IMAGE

Colour Light Output 5,200 lumen-3,952 lumen (economy)
White Light Output 5,200 lumen - 3,952 lumen (economy)

Resolution WUXGA, 1920 x 1200, 16:10

Contrast Ratio 5,000 : 1

Lamp 380 W, 2,500 h durability, 4,000 h durability (economy mode)

Keystone Correction Manual vertical: ± 30 °, Manual horizontal ± 30 °

High Definition Full HD
Aspect Ratio 16:10
Colour Processing 10 Bits

OPTICAL

Projection Ratio 1.26 - 2.30:1

Zoom Manual, Factor: 1 - 1.8

Lens Shift Manual - Vertical ± 67 %, horizontal ± 30 %

Projection Size 50 inches - 300 inches
Projection Distance Wide 1.4 m - 8.4 m (300 inch screen)
Projection Distance Tele 2.5 m - 15 m (300 inch screen)

Projection Lens F Number 1.65 - 2.55

Focal Distance 21.28 mm - 37.94 mm

Focus Manual
Projection Lens Zoom Ratio 1 - 1.8 : 1
Lens Optical

CONNECTIVITY

Interfaces HDBaseT, Cinch audio out, Stereo mini jack audio in (4x), Stereo mini jack audio out, S-Video

in, BNC in, Composite in, Display Port, HDMI in, VGA out, VGA in, Wireless LAN IEEE 802.11b/g/n (optional), Ethernet interface (100 Base-TX / 10 Base-T), RS-232C

COZ.TTB/g/T (Optional), Ethernet interface (100 base-17/ 10 base-1), 110-202

ADVANCED FEATURES

Features Frame interpolation, Freeze image, Instant on/off, Network administration, Network image

transmission, Split-Screen-Function

Security Kensington lock, Security bar

OTHER

Warranty 36 months On site service or 15,000 h, Lamp: 36 months or 1,000 h

Optional warranty extension available

LOGISTICS INFORMATION

| SKU | V11H700041 |
|--------------------------|--------------------|
| EAN code | 8715946548616 |
| Dimensions Single Carton | 762 x 432 x 324 mm |
| Carton Weight | 12.9 Kg |
| Multiple Order Quantity | 1 Units |
| Country of Origin | China |
| Pallet Size Euro | 7 Units |
| Pallet Size Block | 7 Units |

EB-G6570WU

WHAT'S IN THE BOX

- Remote control incl. batteries
- User manual (CD)
- Power cable
- Lens cap
- HDMI Cable Clamp
- Computer cable
- Cable cover

OPTIONAL ACCESSORIES

- 3D Polarizer ELPPL01 V12H618A01
- Wireless LAN Adapter (b/g/n) ELPAP07 V12H418P13
- Quick Wireless Connect USB key ELPAP09 V12H005M09
- Ceiling Mount (White) ELPMB22 V12H003B22
- Lamp ELPLP76 V13H010L76Air Filter - ELPAF4:
- Air Filter ELPAF43
 V13H134A43

OPTIONAL LENSES

- Lens (ST Off Axis) ELPLU01 V12H004U01
- Lens (Rear Wide) ELPLR03 V12H004R03
- Lens (Middle Throw 2) ELPLM05 V12H004M05
- Lens (Middle Throw 1) ELPLM04 V12H004M04
- Lens (Long Throw) ELPLL06 V12H004L06





For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate. Web: www.epson.co.uk www.epson.ie

1. - Requires additional ceiling mount 2 - Except ELPLS05

