





Enjoy interactive teaching with the latest ultra-short throw projector



The Epson EMP-400We is ideal for use in interactive teaching with whiteboards. Easy to use and flexible, this projector allows wide screen presentations with a short projection distance.

Enjoy multimedia at its best and improve interactivity with your students.

### Perfect for use with interactive whiteboards

The Epson EMP-400We is perfectly suited for installation with interactive whiteboards. With digital whiteboards teachers can capture notes and instantly save, publish, print and email. Teachers can improve interactivity with students.



Take advantage of maximum space for teachers and students. Easy to install and to monitor, this ultra-short throw projector is able to display a sharp focused 60-inch picture from a distance of just 65 cm from the projection surface, eliminating shadow effects caused by people and objects in front of the screen.





With the Epson EMP-400We



## Easy maintenance with network monitoring and control

The Epson EMP Monitor<sup>™</sup> software enables you to remotely configure and operate the projector over your network. You can even set an e-mail alert for the internal temperature of your projector, or to monitor lamp status, in order to prevent any possible problems disrupting your presentations.





### Ultra-secure, enhanced anti-theft features

The Epson EMP-400We is equipped with special security features, which mean that if stolen, it becomes useless. The projector requires a password and can only be switched on with a remote control.

To prevent unauthorised use, just keep the password confidential and the remote control in a safe place.

In addition, each time the projector is turned on, and whenever it has no input to display, a warning message appears.



# Ultra-secure, multimedia capabilities, cost efficient – ideal for classrooms

- Ultra-short throw lens, only a small distance to the screen is necessary to project powerful images. This eliminates shadow effects and allows more space for the teacher and students.
- Project a **wide-screen image**, perfect for use with any laptop or with a DVD player.
- **Improved security** with the inclusion of a tough security bar, Kensington lock connectivity and password protection.
- Bright, colourful images with Epson 3LCD technology.

Serial number tracking

is available on this product.

- Exclusive E-TORL lamp. Save money and energy with Epson's exclusive E-TORL lamp technology. These low-wattage lamps combine very high brightness with ultra-low power consumption.
- Easy maintenance with network monitoring and control. The EMP-400We enables teachers and IT support staff to monitor and control the projector simply by entering its IP address into the Epson EMP Monitor<sup>™</sup> software.

Powerful built-in 10W speakers play any audio or video to your audience, without external speakers.



Warning message: "If you see this projector outside an educational establishment it may be stolen".

> No panel buttons can only be used with a remote control.

EPSON

**Easy maintenance** with the Easy-Grab air filter and simple lamp change.

**Ultra-short throw lens** only a small distance is required between the projector and the screen. Thanks to the ultra-short throw projector, your presentation is free of shadows.

**Power on password protection.** The password can only be entered with the remote control. 1800lm 🔆 E-TORL 💽 3.6Kg WXGA 🗰 💒 🕼 10W

#### http://www.epson.co.uk





Model	Epson EMP-400We			
Specifications				
Ordering Information	V11H281T40			
Projection system (3LCD)	0.56-inch with MLA (x3) TFT			
Native Resolution	WXGA (1280x800)			
Native format				
	16:10 (automatic 4:3 / 16:10 / 16:9 detection & resizing )			
Resolution supported	VGA ~ UXGA			
Brightness	High/Low brightness mode: 1800 ANSI Im / 1420 ANSI Im			
Projection lens				
F Number	1.8			
Focal Length	6.48 mm (0.97m)			
Focus/Zoom type	Manual Focus / 1.35 X Digital Zoom			
Offset	10:-1.5			
Lens protection	Lens cover			
Lamp	Type: 170W UHE (E-TORL)			
Lamp	Life: (Low/High brightness mode) 4000 hours / 3500 hours			
Colour Poproduction				
Colour Reproduction	Full-Colour (16.77 million colours)			
Fan noise	Low/High brightness mode: 28 dB / 35 dB			
Contrast ratio	500:1			
Screen size (Projection distance)	50 to 110 inch (0.54 to 1.22m)			
Throw ratio	0.51-0.69 (16:10) / 0.61-0.83 (4:3)			
Keystone correction	Vertical: -15 to +15 degrees			
Input				
Computer	2xD-sub 15-pin (RGB)			
Video	2xD-sub 15-pin (component), 1xRCA, 1xS-Video			
Audio	2xStereo mini-jack, 2xRCA (White/Red)			
Output				
	Computer / Audio: 1xD-sub 15-pin / 1xStereo mini-jack			
Built-in speaker	10 W monaural			
Control	RS-232C			
Network	1xRJ45 (LAN)			
Direct Power On/Off	Yes			
Security	Password Protected Function. Security bar/Padlock and Kensington lock hole			
Other functions	Source Search, Auto Detection of RGB, Operation Panel Protected Function, 8 Colour Modes, High Altitude Mode, User logo, Freeze, A/V Mute, E-Zoom, Help			
Operating temperature / altitude	5°C to 35°C / 0 to 2,286m (High Altitude Mode over 1500m)			
Power supply wattage	100 - 240 V AC ±10%, 50/60 Hz			
Power consumption lamp on	236W			
	23000			
(220/240 V area)				
Power consumption stand-by	5.5W (network off) / 6.4W (network on)			
(220/240 V area)				
Weight	3.6 kg			
Dimension (D x W x H)	258 x 327 x 95 mm (excluding feet)			
On-screen menu	24 languages			
	(English / French / German / Italian / Spanish / Portuguese / Russian / Swedish / Norwegian / Finnish / Danish / Dutch / Hungarian / Czech / Polish / Slovenian / Romanian / Turkish / Greek / Arabic / Japanese / Simplified Chinese / Tradition)			
Network performance	Projector control and projector management via network			
Function	E-Mail notification			
	SNMP			
	Web control			
	PJ-Link			
Software				
oonnalo	EMP Monitor (for Windows) / EPSON Projector Control (for Windows)			
Supplied Accessories Security Pack	- Informations and instructions - Warning stickers			
	- Warning posters			
Power Cable	3m			
Computer Cable	1.8 m D-sub 15pin (Male) - D-sub 15pin (Male)			
Lens cover	included			
Remote Control	With 2xAA type alkaline batteries			
Epson Projector Software (CD-ROM)	included			
,	included			
Password Protect Sticker				
Password Protect Sticker				
Password Protect Sticker User Manual Warranty	included 3 years including lamp			



Telephone: 08702 416900 (UK) 1 800 409132 (Republic of Ireland) E-mail: info@epson.co.uk www.epson.co.uk www.epson.ie Fax: +44 (0) 8702 413093 95 mm

### Front view



Screen size and projection distance



	Projection distance 16:10 aspect ratio					
Screen	Wide		Te	ele		
size	cm	inch	cm	inch		
50	54	21	73	29		
60	65	26	89	35		
70	76	30	104	41		
80	88	34	119	47		
90	99	39	135	53		
100	110	43	150	59		
max 110	122	48	165	65		

	Projection distance 4:3 aspect ratio					
Screen	Wide		Te	ele		
size	cm	inch	cm	inch		
55	67	26	92	36		
60	73	29	100	40		
70	86	34	118	46		
80	99	39	135	53		
90	112	44	152	60		
max 97,2	122	48	165	65		

EPSON® is a registered trademark of SEIKO EPSON® Corporate. All other product names and other company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. Screen images are simulated.

