

Huge brightness and convenience within reach

Do you need high brightness but only have minimal money to spend? The InFocus IN120a Series has that covered and a lot more.

These value-packed projectors are easy to buy and provide multiple ways to display your content -- even without a computer. Plus, their high contrast ratio and BrilliantColor™ technology display outstanding images and its lightweight design makes them easy to move or install.



IN122a

SVGA
(800 x 600)
3500 lumens

IN124a

XGA
(1024 x 768)
3500 lumens

IN126a

WXGA
(1280 x 800)
3500 lumens

Why choose the IN120a Series?

- Ultra-low purchase price
- Brightness of up to 3500 lumens
- Long life lamp of up to 7,000 hours lowers costs even more
- High 15000:1 contrast ratio
- Wireless connectivity with optional USB adapter
- Display over HDMI or USB
- PC-less display from USB drive or 2GB of internal memory
- Present Office docs, video, audio, photos and more wirelessly from your mobile device
- Blu-ray 3D capable (over HDMI)



Connectivity

VGA x 2
HDMI 1.4
USB-A
USB Mini-B
Composite Video

S-Video
RS-232
3.5 mm audio in x 2
3.5 mm audio out
Monitor out (VGA)

Low Total Cost of Ownership

The IN120a Series has not only a low purchase price, but also a lamp that can last as long as 7,000 hours, which lowers total cost of ownership even further. There are no filters to replace either. It's an unbeatable value.

High Brightness and High Contrast

The image quality of these projectors will not disappoint. 3500 lumens will give you bright, clear images with the lights on and the high 15000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface.

Easy Display from Any Device

Built-in apps and optional wireless adapter displays files from an Apple or Android notebook, tablet or smartphone. Or display from no device at all and project images, audio and video from the projector's on-board 2GB of memory.

Eco Blanking

Instantly dim the screen to divert your audience's attention onto you with the Eco Blanking feature on the remote control. Activate this feature when the projector isn't being used and lower the lamp's power usage down to 30%. This saves energy and significantly extends the life of the lamp, which saves you money.

Specifications*

IN122a

IN124a

IN126a

Native Resolution	SVGA 800 x 600	XGA 1024 x 768	WXGA 1280 X 800
Maximum Resolution	WUXGA 1920 x 1200		
Display Technology	DLP 0.55" SVGA, 800x600	DLP 0.55" XGA, 1024x768	DLP 0.65" WXGA, 1280x800
Brightness	3500 lumens Normal Mode (3200 lumens Eco Mode)		
Lamp Life**	3,500 hours (Normal Mode), 5,000 hours (Low Power), 7,000 hours (Eco Blanking***)		
Lamp Power	240W (Normal Mode), 190 (Low Power), 72W (Eco Blanking)		
Contrast Ratio	15000:1		
Color Wheel	6 segment, 2x speed		
Audible Noise	32 dB Normal Mode (30 dB Eco Mode)		
Internal Memory	2 GB		
File Formats Supported	Photo (JPG, JPEG, BMP); Video (at 1080: XVID, MPEG4, H.264, H.263, M-JPEG, WMV3, MPEG-1) (at 720: RV3, RV4); Audio (MP1, MP2, MP3, WMA, OGG, ADPCM-WAV, AAC)		
Documents Supported	PDF, docs from Office 95, 97, 2000, 2003, 2007, 2010		
- via USB drive or internal memory	Adobe PDF 1.6 or later, docs from Office 2003, 2007 or 2010		
- via EZ Display for Android	Adobe PDF 1.6 or later, docs from Office 2003, 2007 or 2010, docs from iWork '09 or later		
- via EZ Display for iOS			
Projection Offset	15%		13%
Keystone Correction	+/- 40° vertical		
Lens Type	Manual zoom and focus		
Lens - Throw Ratio	1.9 - 2.2 (50" @ 2 m)		1.5 - 1.8 (99.6" @ 3.2 m)
- Zoom Ratio	1.1:1		1.2:1
Number of Colors	1.07 billion		
Aspect Ratio	4:3 (Native), Supports 16:9, 16:10, Auto		16:10 (Native), Supports 4:3, 16:9, Auto
Synch - Scan Freq	Horizontal: 15 - 91 kHz / Vertical: 24 - 120 Hz		
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)		
Audio	2 W mono		
Input Sources	HDMI 1.4, VGA x 2, USB-A (for USB thumb drive or wireless network adapter), USB Mini-B (for display over USB and internal memory file management), Composite Video, S-Video, 3.5 mm stereo input x 2, RS-232, USB-B (for control and firmware)		
Output Sources	Monitor out (VGA), Audio out (3.5 mm)		
Control	Projector Keypad, IR Remote, RS-232, USB-B for slide advance		
Product Dimensions - WxDxH	292 x 220 x 108 mm		
Product Weight	3.17 kg		
Shipping Dimensions - WxDxH	330 x 330 x 150 mm		
Shipping Weight	3.67 kg		
Maximum Altitude	3,048 m		
Operating Temperature	32 - 104° F / 0 - 40° C		
3D	Supports 3D content from Blu-ray, cable boxes, dish services and more (over HDMI) at 144Hz. Also supports PC-based content configured at 1080p running at 120Hz. DLP Link 3D glasses required.		
Security Features	Security lock slot, Security bar, User PIN		
Ships with - Accessories	Power cord, VGA cable, Safety instructions, User manual, Remote control		
Warranty	2 year (product), 6 months (lamp), 90 days (accessories)		
Menu Languages	24 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simp. Chinese, Trad. Chinese, Spanish, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic, Vietnamese, Indonesian, Persian, Czech, Romanian, Hungarian)		
Approvals	UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe)		

* Product specifications, terms, and offerings are subject to change at any time without notice.
** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.
*** Eco Blanking hours are determined by a combination of the projector's use in Normal/Low Power modes and while using the Eco Blanking feature.

Wireless Software System Requirements

EZ WiFi (download from projector)
Operating System: Windows XP SP3, Vista SP2, Win 7 SP1 and Win 8 (Starter versions not supported); Mac OS X 10.7 and above
CPU: Windows: Dual Core Intel Core i 1.6 GHz or higher (ATOM not supported); Mac: Dual Core Intel Core i 1.4 GHz or higher (PowerPC not supported)
Graphic card: Intel, nVIDIA or ATI graphic card with 64MB VRAM or above

EZ Display (free download from Google Play store)
Requires Android 4.0 and up

EZ Display (free download from iTunes)
Compatible with iPhone 3GS, iPhone 4, iPhone 4S, iPhone 5, iPod touch (4th generation), iPod touch (5th generation), iPad 2 Wi-Fi, iPad 2 Wi-Fi + 3G, iPad (3rd generation), iPad Wi-Fi + 4G, iPad (4th generation), iPad Wi-Fi + Cellular (4th generation), iPad mini and iPad mini Wi-Fi + Cellular. Requires iOS 5.1 or later. This app is optimized for iPhone 5.

Optional Accessories

Replacement Lamp (SP-LAMP-087)
Universal Ceiling Mount (PRJ-MNT-UNIV)
Wireless Network Adapter (SP-WIFIUSB-2)
LiteShow Wireless Adapter (INLITESHOW3)
LiteShow Mount (PRJ-MNT-LS3)
Soft Carry Case (CA-SOFTCASE-MTG)
Extended warranties (PROJ-EW1YR-V, PROJ-EW2YR-V)



INFOCUS CORPORATE HEADQUARTERS 13190 SW 68th Parkway Portland, Oregon 97223-8368, USA Phone: (1) 503-207-4700 Toll Free: (1) 877-388-8385 Fax: (1) 503-207-4707	INTERNATIONAL HEADQUARTERS 4 Teck Lim Road Singapore 088382 Phone: (65) 6513-9600 Fax: (65) 6238-0535
---	--