

Ultra short throw with big performance and value

Minimise shadows and other distractions with an InFocus IN130UST ultra short throw projector. Place it just cm from the wall and display big, bright, crisp images in high ambient light without shadows or glare.

The IN130UST projectors provide the features you need – such as HDMI, network connectivity, and incredible 3D capability – all for a great price. Plus, its long-lasting lamp will stretch your budget even further.



MODELS

IN134UST

XGA
(1024 x 768)
ULTRA SHORT THROW
(0.437)
2800 LUMENS

IN136UST

WXGA
(1280 x 800)
ULTRA SHORT THROW
(0.35)
3300 LUMENS

Why choose the IN130UST Series?

- Ultra short throw at a great low price
- Up to 3300 lumens of brightness
- Long lamp life of up to 8,000 hours extends the savings
- Deep blacks and bright whites with high 10000:1 contrast ratio
- Extensive connectivity, including HDMI
- Easy to manage over your network
- Microphone input and powerful 20-watt speakers
- Supports every current 3D standard for DLP projectors, plus a 3D Sync port for a 3D IR emitter



Connectivity

HDMI	LAN/RJ45
VGA x 2	VESA 3D Sync Port
Composite Video	RS232
S-Video	Monitor out (VGA)
3.5mm stereo in	USB Type B
3.5mm stereo out	(control & firmware)
3.5mm microphone in	

Minimal Interference

Your content being displayed is king. You worked hard on it, so don't let anything get in the way. The IN130UST projectors minimise shadows and glare since it can produce a 254cm image from only 42cm away.

Ultra Versatile

The IN130UST is compact enough to be mounted or portable. Mount it on the wall to shine on your whiteboard, interactive whiteboard, wall, or screen, or carry or roll it on a media cart from room-to-room. The ultra short throw makes it easy to get a big, sharp image anywhere.

Low Cost of Ownership

The savings for the IN130UST projectors go beyond the low purchase price. They utilize an ultra-efficient lamp that can last up to 8,000 hours, which is easy to do with the projector's bright Eco Mode and low-interference proximity to the wall.

Convenient Connectivity

Connect your digital devices quickly via HDMI, VGA, and more. You can also plug in your microphone for voice lift through the projector's powerful built-in speakers. Network connectivity is also provided for easy monitoring and management.

Specifications*

IN134UST
IN136UST

Native Resolution	XGA 1024 x 768	WXGA 1280 X 800
Maximum Resolution	WUXGA 1920 x 1200	
Brightness	2800 lumens Normal Mode (2400 lumens Eco Mode)	3300 lumens Normal Mode (2800 lumens Eco Mode)
Lamp Life**	5000 hours Normal Mode (8000 hours Eco Mode)	
Lamp Power	230W UHP	
Contrast Ratio	10000:1	
Colour Wheel	6 segment (RGBCYW)	
Input Sources	HDMI 1.4, VGA x 2, Composite Video, S-Video, 3.5 mm stereo input, 3.5 mm microphone input, RS232, USB B (control & firmware)	
Output Sources	Monitor out (VGA), Audio out (3.5 mm)	
Control	Manage over network (RJ45/LAN), Projector Keypad, IR Remote, RS232, USB B for mouse, VESA 3D Sync port (control output)	
Audible Noise	33 dB Normal Mode (29 dB Eco Mode)	
Projection Offset	Fixed +20%	
Keystone Correction	+/- 30° vertical	
Lens Type	Manual zoom and focus	
Lens - Throw Ratio	0.437	0.35
Lens - Zoom Ratio	Fixed	Fixed
Projection Distance	37 - 42 cm	34 - 42 cm
Image Width	173 - 216 cm	203 - 254 cm
Number of Colours	1.07 billion	
Aspect Ratio	4:3 (Native), Supports 16:9, 16:10, Auto	16:10 (Native), Supports 4:3, 16:9, Auto
Synch - Horizontal Scan Freq	31 - 91.4 kHz	
Synch - Vertical Scan Freq	47 - 120 Hz	
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)	
Audio	20W stereo (10W x 2)	
3D	VESA 3D Sync Port for IR emitter and its compatible 3D glasses. Supports all major 3D standards for DLP projectors, including 3D content from Blu-ray, cable boxes, dish services, and more (over HDMI). Also supports PC-based 3D content configured at 720p running at 120Hz signal. DLP Link 3D glasses required.	
Product Dimensions - W×D×H	288 x 375 x 123 mm (not including mirror)	
Product Weight	5 kg (Estimated)	
Shipping Dimensions - W×D×H	440 x 519 x 291 mm	
Shipping Weight	8.5 kg (Estimated)	
Power Consumption	290W Standard, 260W Eco, <0.5W Standby	
Power Supply	100 - 240 V @ 50-60 Hz	
Maximum Altitude	3,048 m	
Operating Temperature	5 - 40° C	
Operating Humidity	5-95% RH without condensation (non-operating)	
Security Features	Security lock slot, Security bar, User PIN	
Ships with - Accessories	Power cord, VGA cable, Safety instructions, User manual, Remote control (without batteries)	
Warranty	2-year product warranty, 6-month limited lamp warranty, 90-day limited accessories warranty	
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Danish, Arabic, Bahasa Indonesian, Brazilian Portuguese, Vietnamese, Turkish, Persian	
Approvals	UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe)	

* Product specifications, terms, and offerings are subject to change at any time without notice.

** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

Optional Accessories

Replacement Lamp (SP-LAMP-084)
 Ultra Short Throw Wall Mount (coming soon)
 LiteShow Wireless Adapter (INLITESHOW3)
 Cables and adapters

For more information, please visit:

www.infocus.com/Accessories

Warranty

Providing the highest quality products and support is very important to us. The IN130UST Series comes standard with a 2-year factory warranty and 6-month lamp replacement warranty. Extended warranty programs are also available.

For more information, please visit:

www.infocus.com/Support/Warranty

InFocus
The New Way to Collaborate