

crystal clear  
display solutions



**FD630U – Full HD**



**WD620U - WXGA**



**XD600U- XGA**

Ultra Bright, User Friendly Projectors;  
Ideal for Business and Education applications.



## Amazing image quality combined with advanced technological design; introducing the FD630U, WD620U and XD600U.

Mitsubishi Electric, a leading manufacturer of innovative, high quality display solutions has introduced three new ultra bright, mobile projectors. Users can choose from three different resolutions to match their specific installation needs (FD630U, 1080p; WD620U, WXGA; XD600U, XGA). Designed for reliability and durability, these projectors incorporate an array of user-friendly functions and advanced technology features. When it comes to visual communications, the FD630U, WD620U and XD600U offer a good balance between cost and features.



## Ecological & Cost-efficient

### Stand-by Mode under 1W

When in stand-by (low) mode, the power consumption is less than 1W, enabling increased energy savings and further contributing to environmental preservation.

### Long 5,000hr Lamp Life

By increasing the estimated lamp life, we've reduced maintenance and operating costs.

### Filter-free design

DLP™ projectors are structurally airtight, eliminating the need for an intake filter. The filter free design also reduces dirt and dust particles from entering the projector, minimising service issues.

## Exceptionally Quiet


### Silent 29dBA Operation

The FD630U, WD620U and XD600U operate at just 29dBA, making these projectors virtually silent for uninterrupted presentations.

## Clear, Vivid Images

### High brightness and high contrast

Ideal for large meeting rooms and conference halls, these projectors offer a high brightness of 4500 ANSI lumens and a high contrast level of 2000:1.



### High-power projection – Distance increased 1.5x

The FD630U, WD620U and XD600U are equipped with a specially calibrated lens for high-power projections. A 60" screen is possible from 1.7 to 2.6m (68in to 102in)\* away from the screen and brilliant, crystal-clear images are assured even when the projection distance is short.

\* XD600U only

## Choose from a Variety of Screen Sizes

### From XGA to 1080p- Select the Resolution that Best Matches Your Needs.

The trend towards wide-screen televisions and wide-screen computers continues to grow. The FD630U and WD620U projectors offer wide-aspect ratios suitable for displaying wide-screen content without distorting or compressing the image. Additionally, switching from an XGA projector to

a WXGA projector increases the display screen area by 1.3. What's more, upgrading to a 1080p projector gives a screen area that is 2.3 times larger compared to XGA.



XGA



WXGA



1080p



## An Array of Convenient Functions

### Top-loading lamp for easier maintenance

The projection lamp is installed in the upper section of the main body. Whether sitting on a shelf or suspended from the ceiling, lamp replacements are made simple and easy, and there is never a need to move the whole projector. A lamp replacement attachment is included to prevent the lamp from being dropped during exchange.




### Loud 10W built-in speaker

A high-volume 10W speaker is built-in, eliminating the need for an external speaker.

### Audio Mix functionality

Using the Audio Mix\* feature and wireless microphone (sold separately), the presenter's voice is reproduced loud and clear in real-time

\*Only compatible with stereo mini-jack. Not compatible with RCA jack (L/R) or HDMI.




## Visual PA to broadcast messages

Designed for convenience and utility, the XD600U and WD620U incorporate Visual PA functionality. With this feature, a control room computer, equipped with projector-control software can be used to send simultaneous messages in real time, to a series of projectors connected to the LAN. Messages can be of up to 350 characters long.

The FD630U is equipped with our new Visual PA2 feature, which provides message input/save and voice announcement functions as well. Emergency messages prepared in advance can be sent simultaneously to all projectors connected on the LAN. The software is also capable of changing messages via the keyboard to verbal announcements, increasing the effect of the message. This system is ideal for broadcasting important information to multiple rooms in schools or office buildings.



Control room  
IT manager inputs  
message and sends  
via LAN  
Same message is  
displayed in each  
classroom



### 3D READY\*

Experience the impact and allure of 3D images. This projector supports a 3D experience when users input and display their 3D content and watch the display with optional DLP™ link compatible glasses.

\*XD600U only



# New MOBILE PROJECTOR

FULL HD **FD630U**  
WXGA **WD620U**  
XGA **XD600U**




Brilliant Color™	Color Enhancer	Wall Screen	10W Speaker	User Logo Projection	Password Lock	Instant Shutdown
Long-life Lamp	Low Stand-by Power	Top/Side Loading Lamp	LAN (RJ-45)	HDMI	Closed Caption	Low Fan Noise
Picture Performance		Presentation		User-friendly		



## Input and Output Terminals

(XD600U/WD620U only)



- 1 Audio output
- 2 Audio input
- 3 S-Video/Video
- 4 HDMI
- 5 PC/Component video input
- 6 Monitor output
- 7 Serial RS-232C
- 8 LAN (RJ-45)

## Specifications


Model	FD630U	WD620U	XD600U
Display technology	0.65" 1-chip DMD	0.65" 1-chip DMD	0.7" 1-chip DMD
Resolution	1920 x 1080 (total 2,073,600 pixels)	1280 x 800 (total 1,024,000 pixels)	1024 x 768 (total 786,432 pixels)
Brightness	4000lm	4000lm	4500lm
Contrast ratio	2000 : 1	2000 : 1	2000 : 1
Picture size	40" - 300"	40" - 300"	40" - 300"
Throw ratio	1.4 - 2.1	1.5 - 2.2	1.4 - 2.1
Source lamp	230W (shut-off time 5000hr) in low mode, 280W (shut-off time 3000hr) in standard mode		
PC compatibility	640 x 480 - 1920 x 1200, True : 1920 x 1080, sync on green available	640 x 480 - 1280 x 1024, True : 1280 x 800, sync on green available	640 x 480 - 1280 x 1024, True : 1024 x 768, sync on green available
Video compatibility	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 Component video; 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i (1125i 50/60Hz), 1080p (1125p 50/60Hz)	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 Component video; 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i (1125i 50/60Hz)	
Input terminals	RGB; mini D-sub 15pin x 2    Video; RCA x 1, S-VIDEO x 1    Digital; HDMI x 1    Audio; stereo mini jack (ø3.5mm) x 2, RCA jack (L/R) x 1		
Output terminals	RGB; mini D-sub 15pin x 1    Audio; stereo mini jack (ø3.5mm) x 1		
Communication terminal	RS-232C; mini DIN 8pin x 1    LAN; RJ-45 x 1		
Audio speaker	10W mono		
Dimensions (W x H x D)	345 x 129 x 270 mm / 13.6 x 5.1 x 10.6 inch		
Weight	3.8kg / 8.3lbs	3.6kg / 7.9lbs	
Power requirements	AC 100-240V, 50/60Hz		
Optional lamp	VLT-XD600LP		

• Compliance with ISO21118-2005

• All brand names and product names are trademarks, registered trademarks or trade names of their respective holders

## Screen Size and Projection Distance

Side view



The above numbers are approximate, and may be slightly different from the actual measurements.

Screen size chart (FD630U)

Screen (16 : 9)				Distance from screen (L)				Height projected image (Hd)	
Diagonal size	Width (W)	Height (H)		Shortest (Wide)	Longest (Tele)				
inch	cm	inch	cm	inch	m	inch	m	inch	cm
40	102	35	89	20	50	47	1.2	71	1.8
60	152	52	133	29	75	71	1.8	107	2.7
80	203	70	177	39	100	96	2.4	144	3.6
100	254	87	221	49	125	120	3.1	180	4.6
150	381	131	332	74	187	182	4.6	271	6.9
200	508	174	443	98	249	243	6.2	362	9.2
250	635	218	553	123	311	304	7.7	453	11.5
300	762	261	664	147	374	365	9.3	—	—

Screen size chart (WD620U)

Screen (16 : 10)				Distance from screen (L)				Height projected image (Hd)	
Diagonal size	Width (W)	Height (H)		Shortest (Wide)	Longest (Tele)				
inch	cm	inch	cm	inch	m	inch	m	inch	cm
40	102	34	86	21	54	48	1.2	72	1.8
60	152	51	129	32	81	73	1.9	110	2.8
80	203	68	172	42	108	98	2.5	147	3.7
100	254	85	215	53	135	123	3.1	184	4.7
150	381	127	323	79	202	186	4.7	277	7.0
200	508	170	431	106	269	248	6.3	370	9.4
250	635	212	538	132	337	311	7.9	463	11.8
300	762	254	646	159	404	373	9.5	—	—

Screen size chart (XD600U)

Screen (4 : 3)				Distance from screen (L)				Height projected image (Hd)	
Diagonal size	Width (W)	Height (H)		Shortest (Wide)	Longest (Tele)				
inch	cm	inch	cm	inch	m	inch	m	inch	cm
40	102	32	81	24	61	45	1.1	67	1.7
60	152	48	122	36	91	68	1.7	102	2.6
80	203	64	163	48	122	91	2.3	137	3.5
100	254	80	203	60	152	115	2.9	171	4.3
150	381	120	305	90	229	173	4.4	258	6.5
200	508	160	406	120	305	231	5.9	344	8.7
250	635	200	508	150	381	289	7.3	431	10.9
300	762	240	610	180	457	348	8.8	—	—



New publication, effective November 2009 Specifications subject to change without notice.