

NEC L51W LED

Order Code: 60003377

NEC L51W LED Professional Mobile Projector

Get innovative LED technology in an extremely compact and lightweight format and with a very stylish look. The L51W LED is a fully featured mobile projector with a comprehensive input panel as well as an integrated office viewer for PC-less and wireless presentations. Low power consumption and a lifetime of the light source of 20.000 hrs result in a very low total cost of ownership.

An ideal solution for mobile and corporate applications as well as cross-use (private/professional).



Ease of Use - thanks to auto keystone and auto input detection.

Extremely Compact and Lightweight - due to innovative LED technology.

Reduced to the Max - minimalistic design with full connectivity and integrated power supply.

Wide format - for extra space in presentations and video content in native aspect ratio - no quality loss due to format scaling.

Wireless presentation - run presentations and slide shows wireless from your smart phone, tablet or PC.













OUTSTANDING PERFORMANCE

- Optional WLAN For wireless presentation
- **3D Ready** DLP®-link™ technology with 120Hz
- Fast and Reliable LED Technology
- HDMI & USB Input to connect various digital devices
- USB and SD Card Reader for PC-less presentations and slide shows
- Full Office Viewer supporting office file formats, images and video



SPECIAL CHARACTERISTICS

1 GB integrated memory, 3D ready, Auto Power ON/OFF, Auto Power Start, Automatic and manual vertical Keystone Correction ($V = \pm 40^{\circ}$), Digital Zoom, Kensington security slot, Keypad Lock, LED Light Source, Lens Cover, Off-Timer, Optional WLAN, Quick-Start-/Direct-Power-Off Function, SD Card Reader, Tripod thread, USB Display, USB Viewer, Wall Colour Correction



Energy Efficiency

Off-Timer; LED light source with 20.000 hrs life time; Very low power usage

Ecological Materials 100% recyclable packaging; Downloadable manuals

Ecological Standards RoHs compliant; ErP compliant; WEEE

| Technical Specification NEC L51W LED | |
|--------------------------------------|---|
| IMAGE | |
| Native Resolution | 1280 x 800 (WXGA) |
| Brightness 1 | 500 ANSI Lumen |
| Contrast Ratio 1 | 4000:1 |
| Lamp | LED Light Source (no lamp required) |
| Lens | F= 1.5, f= 13.92 mm |
| Projection Factor | 1.4:1 |
| Projection Angle [°] | 13.8 |
| Projection Distance [m] | 0.52 – 3 |
| Screen Size (diagonal) [cm] | Minimum: 43.2 / 17"; Maximum: 254 / 100" |
| Focus Adjustment | Manual |
| Supported Resolutions | 1920 x 1080 (HDTV / 1086 i); 1680 x 1050 (WSXGA+); 1440 x 900 (WXGA); 1400 x 1050 (SXGA+); 1366 x 768 (WSXGA+); 1280 x 1024 (SXGA); 1280 x 960 (QVGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (720 p); 1152 x 870 (MAC); 1152 x 864 (SXGA); 1024 x 768 (XGA); 800 x 600 (SVGA); 720 x 576 (576 i/p); 720 x 480 (480 i/p); 640 x 480 (VGA) |
| Frequency | Horizontal: 30 – 100 kHz; Vertical: 50 – 85 Hz |
| CONNECTIVITY | |
| RGB (analog) | Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) |
| HDMI® | Input: 1 x HDMI® (Deep Color, Lip sync) |
| Video | Input: 1 x RCA |
| Audio | Input: 1 x 3.5 mm Stereo Mini Jack |
| USB | 1 x Type A (USB 2.0 high speed); 1 x Type B |
| Video Signals | PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M |
| SD Card | yes |
| REMOTE CONTROL | |
| Remote Control | Audio Control; Auto Adjust; Digital Zoom; Source Select |
| ELECTRICAL | |
| Power Supply | 100-240 V AC; 50 - 60 Hz |
| Power Consumption [W] | 105 Normal Mode; 70 Eco Mode; 0.5 Power Savings Mode |
| MECHANICAL | |
| Dimensions (W x H x D) [mm] | 226 x 43 x 174 (without lens and feet) |
| Weight [kg] | 1.2 |
| Fan Noise [dB (A)] | 32 / 38 (Eco / Normal) |
| OPTIONAL ACCESSORIES | |
| Optional Accessories | Wireless LAN module NP03LM (Europe, South Africa), NP02LM2 (Middle East, Africa, Ukraine), NP02LM3 (Russia) |
| ERGONOMICS | |
| Safety and Ergonomics | CE; ErP; TÜV GS; RoHS |
| Speakers [W] | 1 x 2 (mono) |
| WARRANTY | |
| Projectors | 3 years pan-European service |
| SHIPPING CONTENT Shipping Contents | Projector; IR remote control; Mini D-SUB Signal Cable; Power Cord; Soft Case; Users Manual on CD-ROM; Quick Setup Guide |

¹ Compliance with ISO21118-2005

