

NEC V311W

Order Code: 60003636

NEC V311W Value Projector

Get the Ultimate 3D Experience with the V311W DLP®Projector. The compact size in combination with light weight makes it easy to place it wherever you need it. With 3100 ANSI lumens brightness and higher contrast this compact projector is recommended for screen sizes of up to 110" diagonal. V311W is Nvidia certified to ensure plug and play operation especially for 3D gaming and 3D photography.

The V311W is the perfect solution for small meeting rooms as well as classrooms.



DELIVERING GENUINE BENEFITS

Control and Monitoring - via RS-232.

Green EcoMode Button - on remote.

Higher Efficiency, Lower Power Consumption - full ErP compliance.

Long Lamp Life - up to 5000 hrs.

Virtual Remote - for direct PC control.

3D ready - future-proof DLP®-Link™ technology with 120Hz and Top/Bottom, 60Hz.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.









OUTSTANDING PERFORMANCE

- Excellent and Brilliant Colours due to VIDI technology
- Contrast 3000:1
- High Brightness 3100 ANSI lumens
- Quick Start Direct Power Off
- 7W Speaker
- Carbon Meter indicating the reduced amount of CO2 emissions by the use of ECO mode



SPECIAL CHARACTERISTICS

3D ready DLP®-Link™, 120Hz and Top/Bottom, 60Hz, 6-segment Colour Wheel, Auto Power Start, BrilliantColor™ and VIDI technology, Carbon Savings Meter, Crestron RoomView, Intelligent Power Management, Long Life Lamp, Manual vertical Keystone Correction (V= ±40°), NaViSet Administrator 2, Plug & Play, Quick-Start-/Direct-Power-Off Function, Virtual Remote for direct PC control, 100% recyclable packaging, Downloadable manuals, RoHs compliant, ErP compliant, WEEE



Energy Efficiency	Intelligent Power	Management
-------------------	-------------------	------------

Ecological Materials 100% recyclable packaging;

Downloadable manuals

Ecological Standards RoHs compliant; ErP compliant; WEEE

IMAGE		
Projection Technology	1 x 1.65 cm (0.65") 2x LVDS DMD Chip	
Native Resolution	1280 x 800 (WXGA)	
Contrast Ratio 1	3000:1	
Brightness ¹	3100 ANSI Lumen	
Lamp	225 W AC	
Lamp Life [hrs]	3000 (5000 Eco Mode)	
Projection Factor	1.55 – 1.7 : 1	
Projection Distance [m]	1.05 - 1.7 . 1	
Screen Size (diagonal) [cm] / [inch]	Minimum: 76: Maximum: 762	
Zoom	Manual Manual	
Focus Adjustment	Manual	
	Up to 1920x1080	
Supported Resolutions	·	
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz	
CONNECTIVITY RGB (analog)	Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin	
HDMI™	Input: 1 x HDMI™ (Deep Color, Lip sync)	
Video	Input: 1 x RCA	
S-Video	Input: 1 x Mini DIN 4-pin	
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo for Video and S-Video Output: 1 x 3.5 mm Stereo Mini Jack	
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)	
LAN	1 x RJ45	
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M	
REMOTE CONTROL Remote Control	Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Free function; Help-function; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Picture Adjust; Picture Mode; Picture Mute; Source Select	
ELECTRICAL		
Power Supply	100-240 V AC; 50 - 60 Hz	
Power Consumption [W]		
Power Consumption [w]	268 max.; 210 Eco Mode; 0.5 Power Savings Mode	
MECHANICAL		
Dimensions (W x H x D) [mm]	310 x 95 x 247 (without lens and feet)	
Weight [kg]	2.5	
Fan Noise [dB (A)]	33 / 37 (Eco / Normal)	
ERGONOMICS		
Safety and Ergonomics	CE; ErP; TÜV GS; RoHS	
Speakers [W]	1 x 7 (mono)	
opeaners [11]	i x i (illullu)	
WARRANTY		
Projectors	3 years pan-European service	
Lamp	6 months, max. 1000 hrs	
SHIPPING CONTENT Shipping Contents	User Manual on CD-ROM (Russian Manual in Hardcopy); Projector; IR Remote Control (RD-448E); Mini D-SUB Signal Cable (1.8 m); Power Cord; Quick Setup Guide; Lens Cap	
ODTIONAL ACCESSORIES		
OPTIONAL ACCESSORIES Optional Accessories	3D Starter Kit (NP01SK3D); DLP-Link 3D Glasses (NP01GL/NP02GL); Lamp (NP18LP); Mouse Receiver (NP01MR); Universal Ceiling Mounts (NP01/02/03/04/05UCM)	

¹ Compliance with ISO21118-2005

