



# Looks aren't everything!



The EP721i not only offers fantastic looks and style but also great performance. Super-bright 2500 ANSI Lumens and great SVGA picture quality with striking realistic colour enhances powerful business presentations and enticing home videos.

- 2500 ANSI Lumens to highlight presentations to the finest detail
- · Designer styling: light, compact at 2kg and as versatile on the move as when installed
- BrilliantColor™ and 2000:1 contrast gives exceptional colour to create crystal clear presentations and video - Optoma 5 Year Colour Guarantee\*
- 5 Year Imager Guarantee providing consistent pixel performance\*\*\*
- Digital and Analogue connectivity, capability includes: DVI, HDMI, 2 x VGA
- Auto power-off feature shuts down the projector when not in use, saving power and increasing lamp life
- Filter-free design for lower maintenance costs


#### Easy to use:

- Fully featured remote control with laser pointer and mouse control
- 5 preset picture modes to adjust the settings to match a variety of different applications
- 15 second start-up and cool down time to reduce both time and money in energy use

- Extensive RS232 Command list for AV installations
- Password Security for added Protection
- Long Lamp Life 3000 hours standard

BrilliantColor™ maximises colour accuracy for deeper saturated colours

Optoma guarantees colour quality will remain as new for 5 years\*





- 1 Laser
- 2 Remote Mouse
- 3 Vertical Keystone Correction
- 4 Volume Control
- 5 Brightness Adjustment
- 6 AV Mute
- 7 Direct Input Source Selection

#### EP721i Connections

- 8 VGA Loop through
- 9 VGA In Component & SCART via adaptor
- 10 DVI-I HDMI and 2nd VGA via adaptor
- 11 S-Video Composite via adaptor
- 12 Audio In
- 13 RS232
- 14 USB (remote mouse)



### **Specifications**

•					
	EP721i				
Native Resolution	SVGA 800 x 600				
Compressed Resolution	Up to UXGA (1600 x 1200)				
Brightness	2500/1500 ANSI Lumens (BRIGHT/STD mode)				
Contrast	2000:1				
Noise Level	30dB				
Lamp Life**	3000/2000 (STD/BRIGHT mode	a)			
Display Technology	Single 0.55" SVGA type X DMD	) chip			
Weight / Dimensions (W x D x H)	2 kg / 259 x 188 x 71.5mm				
Remote Control	Full Function Remote Mouse v	vith Laser and Direct Source selecting			
INPUTS:	DVI-I (HDCP)	HDMI via adaptor			
		2nd VGA via adaptor			
	VGA In	Component via adaptor			
		SCART via adaptor			
	S-Video	Composite via adaptor			
	3.5mm Stereo Jack, USB (rem	ote mouse)			
CONTROL	RS232 3 Pin Mini DIN				
OUTPUTS:	PC 15 Pin D-Sub (monitor loop	-through)			
Audio	1 x 1W Speaker				
Aspect Ratio	4:3 Native, 16:9 Compatible				
Keystone Correction	± 40 Degrees Vertical				
On Screen Display	16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish,				
	Dutch, Russian, Finnish, Swed	ish, Greek, Norwegian/Danish, Hungarian,			
	Czech & Arabic				
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i				
Uniformity	85%				
Displayable Colours	16.7 Million				
Projection Lens	F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus				
Throw Ratio	1.95 ~ 2.15:1 (Projection Distance:Image Width)				
Projection Distance	1.2 - 12m				
Image Size	0.70 - 7.70m (27.49" - 303.12	") Diagonal 4:3			
Horizontal / Vertical Scan Rate	15 - 100kHz / 43 - 85Hz				
Power Supply	100-240V, 50-60Hz with PFC P	ower Supply			
Power Consumption	ver Consumption 237W BRIGHT mode < 10W Standby mode				
	211W STD mode < 10W Standb	y mode			
Operating Conditions	Operating: 5 - 40 °C, 80% Hum	idity (Max), 3000m Altitude (Max)			
Security	One Kensington Lock Port, Pas	ssword Protection			
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, S-Video & Composite adaptor, USB				
	Cable, Full Function Remote, B	atteries x 2, Soft Carry Bag, Quick Start Guide,			
	CD User Manual, Warranty, WE	EE Card			
RoHS	Compliant				
Lamp Warranty	6 months or 1000 hours - which	chever is soonest			
Warranty	Warranty will vary by country.	Please see www.optomaeurope.com or ask			
	your local augustor for datatle				

EP721i Projection Distance 1.2 - 12m (4:3 Aspect Ratio)								
Projection Distance (m)	Max. Horizontal Image size (m)	Min. Horizontal Image size (m)	Max. Screen Height (m)	Min. Screen Height (m)	Max. Diagonal Image Size (m)	Max. Diagonal Image Size (Inch)	Max. Image Offset (m)	
1.20	0.62	0.56	0.46	0.42	0.77	30.31	0.07	
2.00	1.03	0.93	0.77	0.70	1.28	50.52	0.12	
2.50	1.28	1.16	0.96	0.87	1.60	63.15	0.14	
3.00	1.54	1.40	1.16	1.05	1.92	75.78	0.17	
4.00	2.05	1.86	1.54	1.40	2.57	101.04	0.23	
5.00	2.56	2.33	1.93	1.75	3.21	126.30	0.29	
6.00	3.08	2.79	2.31	2.10	3.85	151.56	0.35	
7.00	3.59	3.26	2.70	2.45	4.49	176.82	0.40	
8.00	4.10	3.72	3.08	2.80	5.13	202.08	0.46	
9.00	4.62	4.19	3.47	3.15	5.77	227.34	0.52	
10.00	5.13	4.65	3.86	3.50	6.42	252.60	0.58	
11.00	5.64	5.12	4.24	3.85	7.06	277.86	0.64	
12.00	6.15	5.58	4.63	4.20	7.70	303.12	0.69	

your local supplier for details

For guide purposes only

Colour Guarantee\*

EP721i is capable of 16:9 aspect ratio projection. When projecting a 16:9 image the image sizes, screen height and offset information will differ to that of above.

Optoma recommends Panoview screens

## **Panoview**

www.panoview.eu

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.co.uk