





42WPX1



- Screen Dimension: 105cm (42")
- Fully approved IP56 Weatherproof, Protected against powerful water jets and dust ingress
- Winter Mode: -20 C to +45 C operation
- Robust screen surface with anti-reflective tempered glass
- Impressive picture quality: HD Ready
- Anti-corrosive anodized aluminium cabinet
- Suitable for various indoor and outdoor installations as well as 24/7 applications





42WPX1

Model	42WPX1
EAN Code	4994334246707
Category	Weatherproof
Type	Liquid crystal display monitor
IP rating	IP56*
Screen size (diagonal image)	42" (105 cm)
Active screen area (W x H)	93.0 x 52.3 cm
Aspect ratio	16 : 9
Resolution in pixels	1,366 x 768 (WXGA)
Pixel pitch	0.227 x 0.681 mm
Brightness	500 cd/m ²
Contrast ratio	1,500 : 1
Viewing angle	178° (horizontal and vertical)
Response time	6 ms (grey to grey)
Grey scale value	8 bit
Number of colours	16.7 M
Colour Systems	PAL, NTSC3.58, SECAM
Computer compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA
Input terminals	DHDMI (digital/HDCP)
	D-sub15
	Scart (RGB), Video
	Scart RGB-Albos compatible
Output terminals	2 x RCA (R/L Mono) for Audio
	External speaker output (2 x 6w)
Operating temperature	-20 °C to +45 °C (winter mode)
Storage Temperature	−20 °C to +60 °C
Maximum resilience	100 N/mm²
Voltage	100 – 240 V (50/60 Hz)
Power consumption	200 W
Dimensions (W x H x D)	1,027 x 620 x 167.5 mm
Weight	35.5 kg
Vesa mounting sizes	200 x 200 mm
Colour of cabinet	Silver
Warranty	2 years
Standard accessories	User Manual, Remote control, batteries, power cable
Optional accessories	LCD 200 Bracket, LCD 200 Security bracket
Special features	Anodized aluminum case, Anti reflective tempered glass, 24/7 approved

^{*} IP = Protection class



rechnical specifications subject to change without notice. Date 04/2008								