





MAJOR screen has the same features of the Compact model but guarantees high quality images on bigger dimensions.

This screen is a very good solution for projections to a large audience.

It can be equipped with different types of fabric according to customer's needs.

Available in 4:3 and 1:1 ratios or customized sizes.



False ceiling trim kit (optional - for details see p. 48)

Major with black borders (optional)

















OPTIONAL pag 62-63

DROP OF PROJECTON CLOTH STANDARD FRONT DROP OF PROJECTON CLOTH (optional)


WALL-CEILING BRACKET




HOUSING DIMENSIONS



WALL MOUNTING



CEILING MOUNTING




TECHNICAL SPECIFICATIONS

- Silent motor system provides a smooth and quiet operation

Power: 10 Nm
Speed: 17 rpm
Power supply: 230V / 50 Hz
Consumption: 156 W
Certification: IMQ

- Totally manufactured from aluminium
- Smart design and easy to install
- Housing dimensions: 124x133 mm. (DxH)
- Housing painted with white epoxy powders (RAL 9010)
- White dowel bar: height 35 mm. depth 20 mm.
- Four universal mounting brackets either for ceiling or for wall
- On/off switcher included
- Power cable located at **right** side of the screen housing seen from the front
- Flame retardant projection surfaces classification M1 and B1
- Side black borders of 5 cm. and black dowel bar height 35 mm. depth 20 mm. (optional)
- Screen housing available in different colours (optional)



DIMENSIONS measures in cm					
1:1 Ratio Viewing area (WxH)	4:3 Ratio Viewing area (WxH)		Overall dimensions A - C	Approx. net weight (Kg)	
300 x 300	-		311 - 304	25	
350 x 350	350 x 265		361 - 354	28	
400 x 400	400 x 300		411 - 404	33	
-	450 x 340		461 - 454	37	

PROJECTION CLOTHS					
Front projection surfaces	Gain	Rear projection surfaces **no black borders**	Gain		
White	1.2	Rear Plus	1.1		
Matte White	1.2	Front Rear	0.9		
Microperforated	1.1				

