

1T-TG-620 HDMI Test Generator provides a means to verify the correct operation of HDMI equipment such as monitors and projectors. Any device using an HDMI type input (or DVI-D with appropriate adapter) can be tested using several different types of signals. Provision has been made to embed either a 1Khz internally generated audio sinewave or an externally generated audio signal into the digital bitstream so that the integrity of the audio portion of the HDMI signal can be verified and, in addition, HDCP (High Definition Content Protection) functionality can also be tested thereby insuring that all video, audio and security components of an HDMI compliant display device are functioning properly.

HDMI Test Generator

Model 1T-TG-620

Ű**VON€TASK**



Key Features of 1T-TG-620 HDMI Test Generator

- HDMI v1.2, HDCP 1.1 and DVI 1.0 Compliant
- 1.65Gbps Single Link HDMI Frequency Bandwidth
- VESA EDID v1.3 and EIA/CEA 861 Version 3
- Supports resolutions to WUXGA/60 and 1080p
- Supports Embedded Audio Internal and External
- Infrared Remote Control

Specifications

Audio Input		Environmental	
External Audio	1x S/PDIF Optical Connector	Operating Temperature	0° to +48°C (+32° to +120°F)
Video Output		Operating Humidity	10% to 90%, Non-condensing
HDMI (Note 1)	1x via Type A HDMI Connector	Storage Temperature	-10° to +70°C (+32° to +120°F)
HDMI Transport		Storage Humidity	10% to 90%, Non-condensing
Frequency Bandwidth	1.65Gbps (Single Link)	Power Requirement	
Supported PC Resolution	Up to WUXGA/60	External Power Supply	5VDC@2A
Supported HDTV Formats	480p trough 1080p (Note 2)	Regulatory Approvals	
Audio (Embedded)	1Khz Sine wave Int. or Ext.	HDMI Test Generator	FCC, CE, RoHS
Compliance	HDMI v1.2, HDCP V1.1, DVI 1.0	Power Supply	UL, CUL, CE, PSE, GS, RoHS
Special Feature		Accessories Included	
HDCP Function Check	Via Internal Algorithm	1x AC Power Adapter	US, UK or Euro Type
Video Test Patterns		1x Instruction Manual	
36 Video Patterns	In 8 Groups	1x IR Remote Control	
Control Methods		Product Number	
Local Control	Front Panel via PB Switches	1T-TG-620	HDMI Test Generator
Remote Control	1x Infrared Remote Control	Notes	
Warranty		(1) DVID out is available using optional adapter.	
Limited Warranty	2 Years Parts and Labor	(2) The timing of the 1080i output resolution is very	
Mechanical			compatible with all displays.
Size (H-W-D)	1.2"x4.9"x4.9" (30x125x125mm)	entreal and may not be	
Weight (Net)	0.72lbs (334g)		

Panel Drawings

