

# PJ1158

**HIGH BRIGHTNESS  
MULTIMEDIA PROJECTOR  
WITH KEYSTONE CORRECTION**

## Versatile multimedia projector

The ViewSonic® PJ1158 delivers maximum impact for large-venue presentations. With 4000 LUMENS and 1300:1 contrast ratio (typ.), this PREMIUM PROJECTOR with optional lenses is ideally suited for conference rooms, lecture halls, religious institutions and boardrooms. The PJ1158 is fully-featured with a native XGA 1024 x 768 resolution, advanced image processing, manual lens shift, and horizontal and vertical (auto) keystone correction for perfect images. Network connectivity allows you to REMOTELY CONTROL AND MANAGE YOUR PRESENTATIONS and the 4 x 4-watt SRS® WOW STEREO SPEAKERS give your presentations powerful sound. The security bar and PIN lock guard against theft and unauthorised use. The PJ1158 is the fully-featured choice for dynamic presentations and smooth video entertainment in large venues.



### RAISING THE BAR ON YOUR PRESENTATIONS

#### > Ultimate video source flexibility

Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display.

#### > Network control through RJ-45

Manage and monitor the projector remotely and receive e-mail alerts of projector and lamp status.

#### > Enhanced security features

PIN lock feature allows you to prevent unauthorised use. Kensington® security lock and a security bar allow you to secure the projector to deter theft.

#### > The perfect image in any setting

Digital horizontal and vertical (auto) keystone correction, manual lens shift, and optical zoom ensure the perfect image in any room.

#### > Superior 16-watt stereo sound

Four 4-watt speakers with SRS® WOW technology for panoramic 3D sound.

#### > Easy maintenance

Easy access to the lamp and filter covers even when the projector is mounted.

#### > Optional lenses make installation flexible

Easy-to-install bayonet lens options allow you to project in rooms of virtually any size.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

# PJ1158

## HIGH BRIGHTNESS MULTIMEDIA PROJECTOR WITH KEYSTONE CORRECTION

**ViewSonic®**  
See the difference™ 



<b>PROJECTOR</b>	Type	3 x 0.8" P-Si TFT active matrix with MLA
	Resolution	1024 x 768 XGA native, (max. 1600 x 1200 UXGA compressed)
	Lens	Manual zoom, manual focus, manual lens shift
	Zoom Factor	1.2 (F = 1.7–2.1/f = 24.3mm–29.2mm)
	Digital Keystone	Vertical ± 40°, horizontal ± 20°
<b>DISPLAY</b>	Size	30"–300" (0.76m–7.62m) (Diagonal)
	Throw Distance	0.9m–13m
	Throw Ratio	1.5~1.8:1
	Lamp	285W UHB, 2000/3000 hours <sup>1</sup>
	Brightness	4000 ANSI lumens (typ.)
	Contrast Ratio	1300:1
	Aspect Ratio	4:3 (native), 16:9
<b>AUDIO</b>	Speaker	4 x 4-watt with SRS® WOW technology (virtual surround-sound)
<b>INPUT SIGNAL</b>	Video	RGB analogue, NTSC M, NTSC 4.43, PAL, SECAM, SDTV/EDTV (480i/p, 576i/p), HDTV (720p, 1080i)
	Frequency	F <sub>H</sub> : 31–92kHz; F <sub>V</sub> : 56–120Hz
<b>COMPATIBILITY</b>	PC	Analogue: VGA up to UXGA (compressed), 1024 x 768 @ 60Hz preferred
	Mac <sup>®2</sup>	Analogue: up to SXGA (scaled), 1024 x 768 @ 60Hz preferred
<b>CONNECTOR</b>	PC-RGB (in)	2 x 15-pin mini D-sub
	PC-RGB (out)	1 x 15-pin mini D-sub
	Digital	1 x M1-D (DVI plus USB support)
	Composite Video	1 x RCA jack
	S-Video	1 x 4-pin mini-DIN
	Component Video	1 x RCA set (YPbPr)
	Audio (in)	2 x 3.5mm stereo mini jack (for PC), 2 x RCA set L/R jack (for video)
	Audio (out)	1 x 3.5mm stereo mini jack
	USB	Integrated into universal digital M1-D connector (for mouse control)
	Control	1 x 9-pin D-sub RS-232
	Network	1 x RJ-45
<b>POWER</b>	Voltage	AC 100-264V, 50/60Hz (auto switch)
	Consumption	460W (typ.)
<b>CONTROLS</b>	Basic	Stand-by, menu, input, reset, H/V keystone correction, search, focus, zoom, volume
	OSD	Language, colour balance (R, G, B), sharpness, colour, tint, H/V position, H phase, H size, overscan, colour space, component 3-D-YCS, video NR, PinP input, PinP position, power up input, information, S2-aspect, adjust, power off, power on, search, blank, start up, My screen, My screen size, My screen lock, auto off, audio (volume, speaker, mute), menu position, message
<b>OPERATING CONDITIONS</b>	Temperature	5°C–35°C
	Humidity	10%–85% (non condensation)
<b>NOISE LEVEL</b>	Normal	36dB (typ.)
	Eco mode	30dB (typ.)
<b>DIMENSIONS</b>	(W x H x D mm)	418 x 139 x 319 (physical)
		555 x 244 x 478 (packaging)
<b>WEIGHT</b>	Net	7.1kg
	Gross	11.6kg
<b>REGULATIONS</b>		CE, CB, TÜV/GS, GHOST, UL60950, C-UL, FCC B, C-Tick, NOM, CCC, PSB, WEEE, RoHS
<b>PACKAGE CONTENTS</b>		Projector, power cables, VGA cable, AV cable, remote control, batteries, lens cap, Quick Start Guide (multi-language), ViewSonic Wizard CD (User guide) (multi-language)
<b>OTHER</b>		Lens shift, progressive scan, PIN lock, network control, anti-theft security bar, daylight mode, 16-watt speakers, optional lenses
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

### OPTIONAL ACCESSORIES

- > Replacement lamp RLC-021
- > Universal ceiling mount kit WMK-005
- > Stackable ATA hard shipping case CASE-003
- > Short throw zoom lens TBD
- > Long throw zoom lens TBD



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

#### ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

#### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

#### ViewSonic France

Parc des Barbanniers  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

#### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

#### ViewSonic Belux

#### ViewSonic Denmark

#### ViewSonic Finland

#### ViewSonic Italy

#### ViewSonic MEA

#### ViewSonic Netherlands

#### ViewSonic Norway

#### ViewSonic Spain

#### ViewSonic Sweden

Tel: +32 (0)56 85 26 27

Tel: +45 70 22 11 71

Tel: +358 20 7120 860

Tel: +39 02 73 95 50 22

Tel: +971 (0) 4 88 11 871

Tel: +31 (0)20 491 9254

Tel: +47 (0) 22 88 17 60

Tel: +34 (0) 91 63 05 339

Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> Running Eco mode exclusively can extend lamp life. <sup>2</sup> May require optional Mac adapter.

Copyright © 2007 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS PJ1158-1 05/07-UK

For more product information, visit us on the web at [www.ViewSonicEurope.com](http://www.ViewSonicEurope.com)