

# PJ260D

**ULTRA-PORTABLE  
XGA DLP PROJECTOR**  
WITH BRILLIANTCOLOR™ TECHNOLOGY

## Ultra lightweight

ViewSonic's PJ260D projector is a lightweight DLP powerhouse that delivers top-of-the-line performance. This model offers 2000 lumens and up to 2500:1 contrast ratio to display crisp and precise digital images. Weighing just 1.3kg, this dynamo is a great choice for the road warrior, or any other user who desires an ultra light projector without sacrificing brightness. The native 1024 x 768 XGA resolution, keystone correction and zoom lens ensure that you'll get the best possible image in virtually any setting. While supporting up to 1080i HD signals the PJ260D comes with a suite of valuable soft features like password protection, extended vertical keystone correction, customisable start-up screens and preset colour correction modes. This makes the PJ260D not only one of the brightest projectors in its weight class but also a pretty versatile projector for diverse applications.



### SMALL PACKAGE. BIG PERFORMANCE.

> **Bright in virtually any setting with 2000 lumens**

Packs 2000 lumens in just 1.3kg. It's one of the brightest projectors in its weight class.

> **BrilliantColor™ technology**

Featured with an advanced 5 segment colour wheel and Texas Instrument's latest multi-colour processing BrilliantColor technology the PJ260D delivers significantly more accurate and vibrant colours compared to conventional DLP projectors.

> **Ease of use**

The PJ260D comes with a suite of electronic features to make the set-up process easy. Electronic keystone correction maintains a squared image, while several preset modes adapt to any environment - including chalkboard modes to automatically correct colours on green or black boards. In addition, this projector's automatic signal detection reduces set-up times, while a new button on the remote enables easy toggling between high brightness and true colour mode.

> **Supports HD signals including 720p and 1080i**

Capable of displaying HD signals as well as other video and data sources.<sup>1</sup>

> **Protection & Personalisation**

Assign a PIN code to prevent unauthorised use or theft, and customise your start-up screen to suit your needs.

> **Eco mode extends lamp life**

Extend the life of your lamp up to 3000 hours<sup>2</sup> and reduce noise output.

> **Warranty**

Industry-leading three-year on-site warranty with one-year or 1000 hour lamp warranty.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™ 

# PJ260D

## ULTRA-PORTABLE XGA DLP PROJECTOR WITH BRILLIANTCOLOR™ TECHNOLOGY

**ViewSonic®**  
See the difference™ 



### PJ260D Projection Distance Calculator

SCREENSIZE (Diagonal)		PROJECTION DISTANCE (4:3 Aspect Ratio)	
inch	m	inch	m
34.6-40.7	0.9-1.0	63.0	1.6
43.2-50.8	1.1-1.3	78.7	2.0
64.1-75.3	1.6-1.9	118.1	3.0
106.7-125.2	2.7-3.2	196.9	5.0
213.0-250.0	5.4-6.4	393.7	10.0
255.5-300.0	6.5-7.6	472.4	12.0

Accuracy of the calculations are +/- 5%.  
For additional calculations visit [www.ViewSonicEurope.com](http://www.ViewSonicEurope.com).

### OPTIONAL ACCESSORIES

- > Replacement lamp RLC-033
- > Universal ceiling mount kit WMK-018
- > Wireless G Presentation Gateway WPG-150
- > 3 year lamp warranty extension LSWPY3



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>DLP</b>	Type Resolution Lens Zoom Factor Digital Keystone	0.55" DDR XGA DMD DLP 1024 x 768 XGA native, (1280 x 1024 SXGA compressed) Manual zoom, manual focus 1.17 (F = 2.5-2.74/f = 22.0mm-25.5mm) 80° vertical (± 40°)
<b>DISPLAY</b>	Size Throw Distance Throw Ratio Lamp Brightness Contrast Ratio Aspect Ratio	40"-300" (1.02m-7.62m) (Diagonal) 1.6m-12.0m 1.9-2.27:1 200W, 2000 hours (Eco mode 3000 hours <sup>2</sup> ) 2000 ANSI lumens Up to 2500:1 (max.) 4:3 (native), 16:9
<b>AUDIO</b>	Speaker	1 x 2 watt
<b>INPUT SIGNAL</b>	Video Frequency	RGB analogue, NTSC M, NTSC 4.43, PAL (B, G, H, I, M, N, 60), SECAM (B, D, G, K, K1, L), SDTV/EDTV (480i/p, 576i/p), HDTV (720p, 1080i) F <sub>H</sub> : 15-100kHz; F <sub>V</sub> : 43-120Hz
<b>COMPATIBILITY</b>	PC Mac <sup>®3</sup>	Analogue: VGA up to SXGA (scaled), 1024 x 768 @ 60Hz preferred Analogue: up to SXGA (scaled), 1024 x 768 @ 60Hz preferred
<b>CONNECTOR</b>	PC-VGA Composite Video S-Video Audio USB Power	1 x 15-pin mini D-sub 1 x RCA jack 1 x 4-pin mini-DIN 1 x 3.5mm stereo mini jack 1 x USB Typ B (for service only) 3-pin AC plug (CEE22)
<b>POWER</b>	Voltage Consumption	AC 90-240V, 50/60Hz (auto switch) 225W (max), <8W in Standby
<b>CONTROLS</b>	Basic OSD <sup>4</sup>	Stand-by, menu, input, keystone, resync Picture Menu (brightness, contrast, colour temperature [3 defaults, user RGB], keystone correction, aspect ratio, image [PC, movie, sRGB, user], white intensity, gamma), Computer Image Menu (H/V position, H size, fine tune), Video Image Menu (colour, sharpness, tint), Audio Menu (volume, mute), Setting Menu (OSD position, projection [front, rear, ceiling front, ceiling rear], signal type [video, PC], lamp timer, lamp timer reset, auto off, auto source detection, Eco mode, fan speed, OSD timeout), Option Menu (blank screen, start-up screen, screen capture, password), Language Menu (English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese), factory default reset
<b>OPERATING CONDITIONS</b>	Temperature Humidity	0°C-40°C 10%-80% (non condensation)
<b>NOISE LEVEL</b>	Normal Eco mode	35dB (typ.) 32dB (typ.)
<b>DIMENSIONS</b>	(W x H x D mm)	210 x 65 x 165 (physical) 300 x 180 x 250 (packaging)
<b>WEIGHT</b>	Net Gross	1.3kg 3.8kg
<b>REGULATIONS</b>		CE, CB, GOST-R, Hygienic, TÜV/GS, UL/cUL, FCC-B, CCC, SASO, UK-SEPRO, WEEE, RoHS
<b>OTHER</b>		Brilliant Color Technology, 5-segment colour wheel, unplug and go, customizable start-up screen, +/- 40 degree vertical keystone correction, progressive scan, 3:2 pull down, black/green board colour correction pre-sets, Eco mode
<b>PACKAGE CONTENTS</b>		DLP Projector, 1.8m power cables (Europe [Schuko]/UK), VGA cable, remote control, batteries, lens cap, soft carrying case, Quick Start Guide (multi-language), ViewSonic Wizard CD (User guide) (multi-language)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

#### ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

#### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
1 allée des Bas Tilliers  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

#### ViewSonic France

Parc des Barbannières  
Walnut  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

#### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

#### ViewSonic Belux

#### ViewSonic Denmark

#### ViewSonic Finland

#### ViewSonic MEA

#### ViewSonic Netherlands

#### ViewSonic Norway

#### ViewSonic Spain

#### ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)20 7120 860  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> Optional cables required. <sup>2</sup> Running Eco mode exclusively can extend lamp life up to 3000 hours. <sup>3</sup> May require optional Mac adapter. <sup>4</sup> Some features may not be available on all inputs.