PJD6210-WH

VERSATILE, PORTABLE XGA DLP PROJECTOR

WITH BRILLIANT COLOUR TECHNOLOGY

Digital clarity in a portable projector

ViewSonic's PJD6210-WH DLP® projector delivers amazingly clear images with the digital clarity of DLP's BrilliantColor™ technology. It's ideal for use in the office or bring it home for bigger than life home entertainment. With 2,800:1 dynamic contrast, and 2,200 lumens (max) this powerful projector displays crisp text and vivid images. ViewMatch™ technology adjusts colours perfectly so you enjoy rich, vibrant colours regardless of the setting. Multiple preset presentation modes, an increased ±40 degree digital vertical keystone correction and optical zoom ensure the best possible image regardless of location. With up to 4000 hours of lamp life, low cost replacement lamps, filter-less design and a non-degrading DLP light engine, the PJD6210-WH has one of the best "TOTAL COST OF PROJECTION" ratios in the industry.



OUTSTANDING PRESENTATIONS

> Bright in virtually any setting

Packs 2200 ANSI lumens in just 2.4kgs, and with a high 2800:1 contrast ratio (typ), your presentations are guaranteed to be vibrant even in the brightest office environment.

> BrilliantColor[™] technology

Latest BrilliantColorTM Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 5-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid colour reproduction.

> Low total cost of ownership

Make the most of your projector investment with long life lamps with up to 4000^1 hours lamp life and a filterless dust resistant design that reduces maintenance costs.

> Protect your investment

Assign a PIN code to password protect the projector from unauthorized use or theft.

> The perfect setup convenience

The automatic vertical keystone correction (+/- 40 degrees), aspect ratio adjustment and powerful 1.2x optical zoom ensures a perfect image in any room. Adjustable feet let you adjust the image at even higher viewing angles.

> Industry leading warranty

Enjoy full peace of mind with a generous 3 years on-site product warranty and a limited one year lamp warranty.











PJD6210-WH

DLP Projector with BrilliantColor[™]







Optional Accessories

>	Replacement lamp	RLC-034
>	Ceiling mount kit	WMK-018
>	Wireless G presentation gateway	WPG-150
>	Extended 3 - year lamp warranty	LSWPY3

	n Distance creen	ScreenScreen Size 4:3 Screen	
m	feet	m	Inch
1.2	3.9	0.7~0.8	27.3~30.0
1.5	4.9	0.9~1.0	34.2~37.5
1.8	5.9	1.0~1.1	41.0~45.0
2.0	6.6	1.2~1.3	45.6~50.0
3.0	9.8	1.7~1.9	68.4~74.9
5.0	16.4	2.9~3.2	113.9~124.9
10.0	32.8	6.0~6.4	227.8~249.8

DISPLAY	Туре	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024×768 (native) / SXGA 1280×1024 (compressed)
	Lens	1.1x Manual Optical Zoom / Manual focus
	Keystone	Vertical Digital keystone correction:+/-40 degrees
	Size	30"-300" (Diagonal)/ 0.8m-7.6m
	Throw Distance	1.2m-10m (3.93ft-32.8ft)
	Throw Ratio	1.97:1-2.16:1
	Lamp	180 watt
	Lamp life (Normal / Eco Mode)	3500 / 4000 (hours)
	Brightness	2,200 Lumens
	Contrast Ratio	2800:1
	Aspect Ratio	4:3 (Native) / 16:9
INPUT SIGNAL	Computer and Video	RGB Analogue, NTSC M, NTSC 4.43, PAL(B, D, G, H, I, M, N, 60),SECAM, SDTV/EDTV(480i/p, 576i/p), HDTV(720p, 1080i/p)
	Frequency	Fh:31-79 KHz, Fv:50-85 Hz
COMPATIBILITY	PC	Analogue:VGA up to SXGA(scaled)
	Mac ²	Analogue: up to XGA(scaled)
CONNECTOR	RGB Input	1 X 15-pin mini D-sub
	Composite Input	1 X RCA jack
	Control	1X 9pin D-sub RS232
POWER	Voltage	90~240VAC(Auto Switching), 50/60Hz (universal)
	Consumption	230W (typ) / 9W (Stand-by mode)
CONTROLS	Basic	Standby/On, input, menu
	OSD	Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma Computer Image: Frequency, Tracking, H Position, V Position Video Image: Saturation, Sharpnes, Tint Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Power Saving, Auto Source, ECO Mode, High Altitude, OSD Timeout Advance: Blank Screen, Brilliant Color, Password, Factory Reset
OTHER FEATURES		Off-to-Go, Black/White/Green board colour correction presents, Adjustable fan speed, Eco mode
OPERATING	Temperature	41°F - 95°F(5°C - 40°C)
CONDITION	Humidity	10% - 80% (non-condensing)
	Altitude	0 to + 6,000 ft
NOISE LEVEL	Normal / Eco Mode	34dB / 32dB
DIMENSIONS	(W x H x D mm)	273 x 108 x 215 (physical) 325 x 305 x 183 (packaging)
WEIGHT	Net	2.4 kgs
	Gross	3.7kgs
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
PACKAGE CONTENTS		Projector, Power cable, RGB cable, Remote control, Lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3 years on-site product warranty and a limited one year lamp warranty







ViewSonic Europe Limited/UK

ViewSonic Europe Limit Riverside House 7th Floor 2a Southwark Bridge Road London, SE1 9HA United Kingdom Tel: +44 (0) 207 921 2200 Fax: +44 (0) 207 921 2201

ViewSonic Germany
Martin-Schleyer-Straße 18A Hanns-Martin-Schleyer 47877 Willich

Germany Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10

ViewSonic France Parc des Barbanniers 1 allée des Bas Tilliers 92230 Gennevilliers France Tel: +33 (0) 1 41 47 49 00 Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation 381 Brea Canyon Road ViewSonic Corpora 381 Brea Canyon Road Walnut California 91789-0708 USA Tel: +1 909 869 7976 Fax: +1 909 869 7958

ViewSonic Belux Tel: +32 (0)56 85 26 27 ViewSonic Denmark ViewSonic Finland Tel: +45 70 22 11 71
Tel: +358 (0)20 7120 860 ViewSonic MEA Tel: +971 (0) 4 88 11 871 ViewSonic Netherlands Tel: +31 (0)20 491 9254 ViewSonic Norway Tel: +47 (0) 22 88 17 60 Tel: +34 (0) 91 63 05 339 ViewSonic Spain Tel: +46 (0) 8 50 71 30 00

Running Eco mode exclusively can extend lamp life. ² May require optional Mac adapter.

Copyright c 2007 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS PJD6210-WH 08/08-UK