

PJD6211

DLP® PROJECTOR WITH BRILLIANTCOLOR™

120HZ AND 3D-READY

Price/performance leader in portable DLP® projectors.

ViewSonic's PJD6211 DLP® projector is ideal for use in the office or on the road. It delivers amazingly clear images with the digital clarity of DLP's BrilliantColor™ technology. This budget-friendly projector boasts amazingly fast 120Hz frame rate and is 3D-ready for graphic renderings in the office or 3D games or movies at home. With high contrast ratio and brightness and ViewMatch™ technology to adjust color perfectly, your presentations will be rich, vibrant regardless of the setting. This projector is a lightweight powerhouse that offers multiple inputs, including support for 720p and 1080i HDTV signals. Eco-mode extends lamp life and reduces fan noise. Enjoy easy set up with auto source detection and auto sync. When you're done, just unplug it and go. The PJD6211 DLP® projector delivers excellent performance and value for small business and home entertainment applications.



BRIGHT AND JUST RIGHT

> **BrilliantColor™ technology**

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

> **Closed captioning**

Integrated closed captioning decoder for the hearing impaired.

> **DLP® technology**

Stunning all digital clarity delivers lifelike color, sharp graphics and outstanding video.

> **Eco-mode extends lamp life**

Extend the life of your lamp up to 5,000 hours** and reduce noise output.

> **Off-to-Go feature**

This feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.

> **Bright in virtually any setting with 2,500 lumens**

Packs 2,500 lumens in just 5.9 lbs. It's the bright choice for mobile presenters.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference®

PJD6211

DLP® PROJECTOR WITH BRILLIANTCOLOR™ – 120HZ AND 3D-READY



Optional Accessories

- > Replacement Lamp RLC-050
- > Universal Ceiling Mount Kit WMK-005
- > Wireless G Presentation Gateway WPG-350
- > Soft Case PJ-CASE-001
- > Extended Express Exchange® PRJ-EE-08-03

Projection Distance		4:3 Screen Size			
		Wide		Tele	
M	Feet	M	Inches	M	Inches
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14421-01B-09/09] PJD6211-1

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024x768 (Native) / SXGA 1280x1024 (compressed)
	Lens	1.2x Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	30"-300" / 0.8m-7.6m
	Throw Distance	1.2m-10m / 3.9ft.-32.8ft.
	Throw Ratio	1.6:1-1.9:1
	Lamp	280 watt
	Lamp Life (Normal / Eco-mode)	4000 / 5000* hours
	Brightness	2,500 Lumens
	Contrast Ratio	2000:1 (typ)
	Aspect Ratio	4:3 (native) and 16:9
	Color Depth	24 bits, 16.7M colors (8+8+8)
	Color Wheel	6-Seg RGBCYW / 7200rpm
	Color Gamut	85% NTSC 1931 CIE
INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 31-80KHz, Fv: 50-120Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac®	Up to 1152x864 (scaled)
CONNECTOR	RGB Input	15-pin mini D-sub (x2)
	RGB Output	15-pin mini D-sub
	Composite Input	RCA jack
	S-video Input	4-pin mini-DIN
	Audio Input	3.5mm mini jack
	Audio Output	3.5mm mini jack
	Control	RS-232 (9-Pin D-sub)
	USB	Type B
AUDIO POWER	Speaker	2W
	Voltage	90-240VAC (Auto Switching), 50/60Hz (universal)
CONTROLS	Consumption	235W (typ) / <1W (stand-by mode)
	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	Picture: brightest, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert Computer Image: Frequency, tracking, H. position, V. position Video Image: Saturation, sharpness, tint Setting: Menu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, eco-mode, high altitude, OSD timeout Advance: blank screen, password, screen capture, start up screen Text shot: digital zoom, dynamic contrast ratio, close caption, BrilliantColor
OPERATING CONDITIONS	Temperature	32°F-104°F (0°C-40°C)
	Humidity	10%-90% (non-condensing)
	Altitude	0-6,000 ft (1,800m), operational up to 10,000 ft (3048m) at reduced reliability and performance
NOISE LEVEL	Normal / Eco-mode	31dB / 29dB
	Physical	11 x 4.5 x 8.6 (in) / 280 x 114 x 218 (mm)
DIMENSIONS (W x H x D)	Packaging	13.6 x 8.7 x 12 (in) / 345 x 305 x 220 (mm)
	Net	5.86 lb (2.6 kg)
WEIGHT REGULATIONS	CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC	
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com