

PJD6241

LIGHT BRIGHT AND PORTABLE PROJECTOR

120HZ, 3D-READY

Digitally clear, dynamic presentations

The PJD6241 is the lightweight BrilliantColor™ projector that is a feature-rich performer delivering more vibrant colors and crisp, sharp images. With support for 120Hz frame rates, this high brightness projector is ready for 3D business, education or gaming applications. Remotely manage and schedule your projector through the RJ-45 network control. Deliver a truly dynamic multimedia experience with the extensive input options, including two RGB inputs and one RGB output, and integrated 2x5-watt stereo speakers. Using less than 1 watt of power in standby mode, the PJD6241 is environmentally friendly as well. The conveniently placed lamp access and filter-free makes maintenance a breeze. Up to 6000 hours of lamp life, low cost replacement lamps, filter-less design and a non-degrading DLP light engine, the PJD6241 has one of the best "TOTAL COST OF PROJECTION" ratios in the industry.



> BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid color reproduction.

> Advanced connectivity

In addition to standard connectors, this projector provides two RGB inputs to easily switch between presenters and an additional RGB output to connect to an external monitor. An additional RJ45 input plus audio in/out give even more connectivity options.

> Eco-mode extends lamp life

Extend the life of your lamp up to 6000 hours** and reduce noise output.

> Network control through RJ-45

Remotely schedule, manage and monitor the projector and its lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.

> Off-to-Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™

PJD6241

LIGHT BRIGHT AND PORTABLE PROJECTOR



Optional Accessories

- >Replacement lampRLC-049
- >Wireless presentation gatewayWPG-350
- >Universal ceiling mountWMK-018
- >Universal soft casePJ-CASE-001

Projection Distance		4 : 3 Screen			
		Screen Size			
		Wide		Tele	
M	feet	m	inch	m	inch
1.5	4.92	0.99	38.85	0.89	35
1.8	5.90	1.18	46.62	1.07	42
2	6.56	1.32	51.80	1.19	47
3	9.84	1.97	77.70	1.79	70
5	16.40	3.29	129.51	2.98	117
10	32.80	6.58	259.01	5.95	234



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Model No.VS12476

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024×768 (Native) / SXGA 1280×1024 (compressed)
	Lens	1.2× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Display Size (diagonal)	30" -300"
	Throw Distance	1.2m-12m / ft-ft
	Throw Ratio	1.7 - 2.1:1
	Lamp	230watt (RLC-049)
	Lamp Life (Normal / Eco Mode)	4000 / 6000 (hours)
	Brightness	3400 Lumens
	Contrast Ratio	3000:1 (with DCR)
	Aspect Ratio	4:3 (native) & 16:9
	Color Depth	24 bits, 16.7M Colors (8+8+8)
AUDIO	Speaker	5W×2
	Control	1×RS-232 (9 Pin D-sub) / RJ45
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 31-80 KHz, Fv: 50-120 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 1024×768 (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	RGB Output	1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	2 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1×RS-232 (9 Pin D-sub) / RJ45
POWER	Voltage	90~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	250W (Typical) / <1W (Stand-by mode)
LANGUAGE		English/ Dutch/French / Spanish/Italian/ Korean/Thai/Portuguese/ T. Chines/ S. Chinese /Japanese /Russian /German /Swedish /Turkish / Finnish/Polish
CONTROLS	Basic	POWER, Keystone/Arrow keys, Left/BLANK, MENU/EXIT, Right/Panel key lock, AUTO, MODE/ENTER, SOURCE
	OSD	Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert. Computer Image: Frequency, Tracking, H Position, V Position Video Image: Saturation, Sharpnes, Tint Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset,Power Saving, Auto Source, ECO Mode, High Altitude, OSD Timeout Advance: Blank Screen, Password Word, Screen Capture, Start up Screen, Text Shot, Digital Zoom, DCR, Close Captions, Brilliant Color.
	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10% - 90% (non-condensing)
	Altitude	0~1,800m (6000ft), operational up to 3,048m (10000ft)
	Normal / Eco Mode	30dB / 30dB
	Physical	280 × 114 × 218 (mm) / 11 × 4.25 × 8.58 (inch)
	(W × H × D)	
	Net	2.7 kg (5.95 lb)
	Net	
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKRSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Soft case, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Rev.1.0

ViewSonic Europe Limited/UK
Tower 42
25 Old Broad Street
London EC2N 1HQ
United Kingdom

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. PJD6211

For more product information, visit us on the web at viewsoniceurope.com