

PJL7201

BRIGHT 3LCD PROJECTOR

WITH ADVANCED CONNECTIVITY

Feature packed, versatile, reliable

ViewSonic's PJL7201 features the latest LCD panels, 2,600 lumens and native 1024x768 XGA resolution to deliver clear and crisp images and smooth video performance even in well lit environments. The PJL7201 is very flexible with built-in automatic digital keystone correction and better than average optical zoom function, projecting square images from almost any angle. A wide range of connectors, including DVI with HDCP support and the remote control with mouse function make it easy to deliver dynamic presentations. The PJL7201 offers a PIN lock function to protect your investment and includes many other features like 10-bit gamma correction, customizable start-up screen and easy lamp replacement. The PJL7201 offers an impressive set of features at affordable cost which make it the perfect choice for applications in education, institutions and corporations.



OUTSTANDING PRESENTATIONS

- > **Bright in virtually any setting**
Packs 2600 ANSI lumens in just 7.9 lb (3.6 kg), and with a high 650:1 contrast ratio, your presentations are guaranteed to be vibrant even in the brightest office environment.
- > **Short-throw lens for large, stunning images in small spaces**
The short throw lens enables large images to be projected from short distances in small rooms with short throw distances. A screen size of 50" is possible from just 1.4m.
- > **The perfect setup convenience**
The automatic vertical keystone correction (+/- 30 degrees), aspect ratio adjustment and powerful 1.2x optical zoom ensures a perfect image in any room. Adjustable feet let you adjust the image at even higher viewing angles.
- > **Easy, cost-effective maintenance**
The sliding filter cover and simple lamp replacement from the side of the unit make maintenance a breeze, even when the projector is mounted.
- > **Advanced connectivity**
In addition to standard connectors, this projector provides one RGB output, component inputs for high quality video performance and a full set of audio in and outputs. The DVI-I input with HDCP input ensures signal integrity for superior HD video and picture quality.
- > **Industry leading warranty**
Enjoy full peace of mind with a generous 3 years on-site product warranty and a limited one year lamp warranty.



PJL7201

Bright 3LCD projector with advanced connectivity



Optional Accessories

- > Replacement lamp RLC-041
- > Ceiling Mount Kit WMK-018
- > Wireless G presentation gateway WPG-150
- > Extended 3 - year lamp warranty LSWPY3

Projection Distance 4:3 Screen		Screen Size (diagonal) 4:3 Screen	
m	feet	m	Inches
1.2	3.9	0.9-1.0	34.0-40.8
1.5	4.9	1.1-1.3	42.4-50.9
1.8	5.9	1.3-1.6	51.0-61.1
2	6.6	1.4-1.7	56.6-67.9
3	9.8	2.2-2.6	84.8-101.8
5	16.4	3.6-4.3	141.4-169.7
8.8	29	6.6-7.6	250.0-300.0



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom
Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

DISPLAY	Type	0.63" (x3) Poly-Si TFT with Micro Lens
	Resolution	XGA 1024x768 (native) / Full HD 1920x1080 (compressed)
	Lens	1.2x Manual optical zoom / Manual optical focus
	Keystone	Auto vertical digital keystone correction: ± 30 degrees
	Size	40"-300" (Diagonal) / 1.0m-7.6m
	Throw Distance	1.1m-10.5m (43.3"-413")
	Throw Ratio	1.4:1 - 1.7:1
	Lamp	220 w
	Lamp Life (Normal / Eco Mode)	2000 / 3000 (hours)
	Brightness	2600 Lumens
	Contrast Ratio	650:1
	Aspect Ratio	4:3 (native) / 16:9
AUDIO	Speakers	1 x 7w
INPUT SIGNAL	Computer and video	RGB Analogue, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N, 60), SECAM, SDTV / EDTV (480i/p, 576i/p), HDTV (720p, 1080i/p), HDTV (480i/p, 576i, 720p, 1080i/p)
	Frequency	Fh:31-92 KHz, Fv:48-120 Hz
COMPATIBILITY	PC	Analogue: VGA to Full HD
	Mac*	Analogue: Up to XGA (may require Mac Adapter)
CONNECTOR	RGB Input	1 x 15-pin mini D-sub
	RGB Output	1 x 15-pin mini D-sub
	Digital Input	1 x DVI-I
	Composite Input	1 x RCA jack
	S-Video Input	1 x 4-pin mini-DIN
	Component	1 x RCA jack
	Audio Input	2 x 3.5mm mini jack, 1 (L/R) x RCA jack
	Audio Output	1 x 3.5mm mini jack
	Control	1 x RS-232 (9 Pin D-sub)
	USB	1 x USB type B (for mouse control only)
POWER	Voltage	90~120VAC/220~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	255W (Typ.) / <5W (Stand-by mode)
CONTROLS	Basic	Keystone, Vol +/-, Input, Menu, Blank, Auto
	OSD	Picture: <Computer Mode> Brightness, Contrast, Sharpness, Display mode (Natural, Cinema, Daylight, Greenboard, Whiteboard, Blackboard), Color Temp. (High, Mid, Low, User: User Red, User Green, User Blue) <Video Mode> Brightness, Contrast, Sharpness, Display mode, Color Temp. (High, Mid, Low, User: User Red, User Green, User Blue), Color, Tint Audio: Volume, Audio Channel Setting (RGB, DVI-I, Video, S-Video, YPbPc) Image: <Computer Mode> H Position, V Position, Phase, Frequency, Auto Keystone, V Keystone, Resize, Auto Syne, Auto Search <Video Mode> Auto Keystone, V Keystone, Resize, Auto Search Setting: Language (12 languages), Select Source, Logo Setting, Lamp Mode (Normal, Economic), Lamp time, Reset Lamp Timer, Reset Filter Timer, Filter Counter Option: Zoom/ PAN, Still, Blank, Reset All, Auto Ceiling (Front, Ceiling, Rear, Ceiling and Rear) Advanced: PIN Lock Protection, Modify PIN, Auto Brightness, DCR (Dynamic Contrast Ratio), Closed Caption, Blank off, Auto on (lamp on), No signal off
OTHER FEATURES		Short Throw Feature, DVI with HDCP support, Supports Dynamic Contrast ratio, 6 default picture mode for different environment usage, Auto off and on
OPERATING CONDITION	Temperature	41°F-95°F (5°C-35°C)
	Humidity	20%-80% (non-condensing)
	Altitude	0 to +10,000 ft
NOISE LEVEL	Normal / Eco Mode	34dB / 29dB
DIMENSIONS	(W x H x D mm)	325 x 112 x 260 (physical)
		462 x 195 x 359 (packaging)
WEIGHT	Net	3.6 kgs
	Gross	6.3 kgs
REGULATIONS		UL60951-1, cUL, FCC part15 ClassB, CISPR22 ClassB, CISPR24 ClassB, ICES003, IRAM, CB, CE, CCC, Gost-R+ Hyg, UkrSEPRO, NEMKO-GS, SASO, PSB, C-tick, EK, KPS (Korea), RoHS
PACKAGE CONTENTS		Projector, power cords, VGA cable, USB cable, wireless remote control, lens cap, soft case, ViewSonic Wizard CD, Quick Start Guide
WARRANTY		3 years on-site product warranty and a limited one year lamp warranty

* May require optional Mac adapter.

Copyright © 2007 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS PJL7201 09/08-UK

For more product information, visit us on the web at viewsoniceurope.com