



## Ultra mobile digital projector for brilliant presentations

The Vivitek D519 digital projector is ready for current and future media applications. With connectivity options including HDMI v.1.3, the D519 is 3D ready via DLP link for entertainment, features a high brightness of 3000 ANSI Lumens and a 15000:1 contrast ratio. The D519 is able to deliver sharp, vibrant pictures. The new high efficiency lamp that lasts up to 6000 hours makes the D519 an economic projector to run.

### Features

- Native XGA (1024 x 768) resolution
- Super bright at 3000 ANSI Lumens for dazzling images
- 15000:1 contrast ratio for amazing picture quality
- High-efficiency lamp that last up to 6000 hours
- Connectivity options including: HDMI v.1.3 VGA-In, S-Video, Composite Video, and RS-232C
- 3D-Ready via DLP Link™
- Keypad lock prevents accidental system adjustments
- Ultra mobility thanks to light weight of 1.9kg

Specifications	
Brightness	3000 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	UXGA (1600 x 1200)@60Hz
Contrast Ratio	15000:1
Lamp Life and Type	4000 /6000 Hours (std. / Boost. Mode),190W
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.92 - 2.14:1
Image Size (Diagonal)	40" - 300"
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F = 2.52 - 2.73, f = 24.34 - 25.95mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native, 16:10, 16:9 Compatible
Offset	128%
Keystone Correction	±30° Vertical
Horizontal Frequency	15, 30 - 90kHz
Vertical Scan Rate	43 - 85Hz
Speakers	2 Watt Mono
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v.1.3, VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), RS-232C
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x H)	261 x 190 x 78mm (10.28" x 7.48" x 3.07")
Weight	1.9kg
Noise Level	30dB/33dB (Std. / Boost. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	230W (Std. Mode), 260W (Boost Mode), <1W(Standby)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case

### Photos

