





Mobile Digital Projector for Great Presentations

The Vivitek D551 digital projector is ready for current and future media applications. With connectivity options including VGA-in (2x) and VGA-out loopthrough Composite, Audio-in/out, the D551 is also 3D ready via DLP link for entertainment, features a high brightness of 3000 ANSI Lumens and a 15000:1 contrast ratio. The D551 is able to deliver sharp, vibrant pictures. The new high efficiency lamp that lasts up to 10,000 hours, which makes the D551 an economic projector to run.

Features

- High 15,000:1 contrast ratio ensures a crisp and sharp image
- Superior 3,000 ANSI lumens for projection in even well-lit rooms
- DLP® BrilliantColor™ technologies for excellent color reproduction
- Native XGA resolution with display up to UXGA (1600 x 1200)@60Hz
- Connectivity options including: VGA-In, S-Video, Composite Video, and RS-232C
- 3D-Ready via DLP Link™
- Audio ready with built-in 2 watt audio speaker
- Convenient top loading design for easy lamp replacement
- Energy consumption is reduced to less than 0.5W in stand-by mode
- Keypad lock prevents accidental system adjustments
- 2.3kg for easy portability

Product Pictures









Display Type DLP® BrilliantColor™ Technology Brightness 3000 ANSI Lumens Native Resolution XGA (1024 x 768) Maximum Resolution UXGA (1600 x 1200)@60Hz Contrast Ratio 15000:1 Uniformity 95% Lamp Life and Type 5,000/6,000/10,000 Hours (Std./Eco/Dyn.Eco Mode) Throw Ratio 1.92-2.14:1 Image Size (Diagonal) 23"-256" Projection Distance 1 - 10m (3.28ft - 32.8ft) Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Vertical ± 40° (±40 Step) Horizontal Frequency 2D: 15,30 - 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 - 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480), 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), RS-232, MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-	Specifications	
Brightness 3000 ANSI Lumens Native Resolution XGA (1024 x 768) Maximum Resolution UXGA (1600 x 1200)@60Hz Contrast Ratio 15000:1 Uniformity 95% Lamp Life and Type 5,000/6,000/10,000 Hours (Std./Eco/Dyn.Eco Mode) Throw Ratio 1.92-2.14:1 Image Size (Diagonal) 23"-256" Projection Distance 1-10m (3.28ft – 32.8ft) Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Vertical ± 40° (±40 Step) Horizontal Frequency 2D: 15,30 – 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 – 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount	•	DLP® BrilliantColor™ Technology
Native Resolution XGA (1024 x 768) Maximum Resolution UXGA (1600 x 1200)@60Hz Contrast Ratio 15000:1 Uniformity 95% Lamp Life and Type 5,000/6,000/10,000 Hours (Std./Eco/Dyn.Eco Mode) Throw Ratio 1.92-2.14:1 Image Size (Diagonal) 23"-256" Projection Distance 1-10m (3.28ft – 32.8ft) Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Vertical ± 40° (±40 Step) Horizontal Frequency 2D: 15,30 – 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 – 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, X1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions		
Maximum Resolution UXGA (1600 x 1200)@60Hz Contrast Ratio 15000:1 Uniformity 95% Lamp Life and Type 5,000/6,000/10,000 Hours (Std./Eco/Dyn.Eco Mode) Throw Ratio 1.92-2.14:1 Image Size (Diagonal) 23"-256" Projection Distance 1-10m (3.28ft – 32.8ft) Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Vertical ± 40° (±40 Step) Horizontal Frequency 2D: 15,30 – 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 – 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington* Security Slot, Keypad Lock Dimen	•	
Contrast Ratio 15000:1 Uniformity 95% Lamp Life and Type 5,000/6,000/10,000 Hours (Std./Eco/Dyn.Eco Mode) Throw Ratio 1.92-2.14:1 Image Size (Diagonal) 23"- 256" Projection Distance 1 -10m (3.28ft – 32.8ft) Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Vertical ± 40° (±40 Step) Horizontal Frequency 2D: 15,30 – 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 – 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <		,
Uniformity 95% Lamp Life and Type 5,000/6,000/10,000 Hours (Std./Eco/Dyn.Eco Mode) Throw Ratio 1.92-2.14:1 Image Size (Diagonal) 23"-256" Projection Distance 1-10m (3.28ft – 32.8ft) Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Vertical ± 40° (±40 Step) Horizontal Frequency 2D: 15,30 – 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 – 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington* Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <		, , -
Lamp Life and Type		
Throw Ratio Inage Size (Diagonal) 23"- 256" Projection Distance 1 -10m (3.28ft – 32.8ft) Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Horizontal Frequency Vertical ± 40° (±40 Step) Horizontal Frequency Vertical Scan Rate 24 - 30Hz, 47 – 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz 240W (Normal Mode), 200W (Eco Mode) -0.5W (Standby Mode) Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	,	5.000/6.000/10.000 Hours (Std./Eco/Dvn.Eco Mode)
Image Size (Diagonal) 23"-256"		
Projection Distance Projection Lens F = 2.52 - 2.73, f = 21.8 - 24mm Zoom Ratio 1.1x Aspect Ratio 4:3 Native Offset 128% ± 10% Keystone Correction Horizontal Frequency 20: 15,30 - 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 - 120Hz Speakers 2W (Mono) 3D Ready Video Compatibility Video Compatibility VGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) Weight 2.3kg Noise Level Power Supply AC 100-240V, 50/ 60Hz Power Consumption VGA-In (x2), VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer		
Projection LensF = 2.52 - 2.73, f = 21.8 - 24mmZoom Ratio1.1xAspect Ratio4:3 NativeOffset128% ± 10%Keystone CorrectionVertical ± 40° (±40 Step)Horizontal Frequency20: 15,30 - 91.4kHz/3D: 101.6kHzVertical Scan Rate24 - 30Hz, 47 - 120HzSpeakers2W (Mono)3D ReadyYes (via DLP Link)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)Projection MethodTable Top, Ceiling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (W x D x H)274.6x 212 x 100mmWeight2.3kgNoise Level35dB/32dB (Normal/Eco Mode)Power SupplyAC 100-240V, 50/ 60HzPower Consumption240W (Normal Mode), 200W (Eco Mode)-0.5W (Standby Mode)Warranty2-Year Warranty, 1-Year or 1,000h Lamp WarrantyStandard AccessoriesAC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation KitOptional AccessoriesReplacement Lamp, Remote w/ Laser Pointer	, , ,	
Zoom Ratio1.1xAspect Ratio4:3 NativeOffset128% ± 10%Keystone CorrectionVertical ± 40° (±40 Step)Horizontal Frequency2D: 15,30 – 91.4kHz/3D: 101.6kHzVertical Scan Rate24 - 30Hz, 47 – 120HzSpeakers2W (Mono)3D ReadyYes (via DLP Link)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)Projection MethodTable Top, Ceilling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (W x D x H)274.6x 212 x 100mmWeight2.3kgNoise Level35dB/32dB (Normal/Eco Mode)Power SupplyAC 100-240V, 50/ 60HzPower Consumption240W (Normal Mode), 200W (Eco Mode)-0.5W (Standby Mode)Warranty2-Year Warranty, 1-Year or 1,000h Lamp WarrantyStandard AccessoriesAC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation KitOptional AccessoriesReplacement Lamp, Remote w/ Laser Pointer	•	
Aspect Ratio Offset 128% ± 10% Keystone Correction Vertical ± 40° (±40 Step) Horizontal Frequency 2D: 15,30 – 91.4kHz/3D: 101.6kHz Vertical Scan Rate 24 - 30Hz, 47 – 120Hz Speakers 2W (Mono) 3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Emissington® Security Slot, Keypad Lock Dimensions (W x D x H) Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	•	
Offset128% ± 10%Keystone CorrectionVertical ± 40° (±40 Step)Horizontal Frequency2D: 15,30 – 91.4kHz/3D: 101.6kHzVertical Scan Rate24 - 30Hz, 47 – 120HzSpeakers2W (Mono)3D ReadyYes (via DLP Link)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)Projection MethodTable Top, Ceiling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (W x D x H)274.6x 212 x 100mmWeight2.3kgNoise Level35dB/32dB (Normal/Eco Mode)Power SupplyAC 100-240V, 50/ 60HzPower Consumption240W (Normal Mode), 200W (Eco Mode)-0.5W (Standby Mode)Warranty2-Year Warranty, 1-Year or 1,000h Lamp WarrantyStandard AccessoriesAC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation KitOptional AccessoriesReplacement Lamp, Remote w/ Laser Pointer		
Keystone CorrectionVertical ± 40° (±40 Step)Horizontal Frequency2D: 15,30 – 91.4kHz/3D: 101.6kHzVertical Scan Rate24 - 30Hz, 47 – 120HzSpeakers2W (Mono)3D ReadyYes (via DLP Link)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)Projection MethodTable Top, Ceiling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (W x D x H)274.6x 212 x 100mmWeight2.3kgNoise Level35dB/32dB (Normal/Eco Mode)Power SupplyAC 100-240V, 50/ 60HzPower Consumption240W (Normal Mode), 200W (Eco Mode)-0.5W (Standby Mode)Warranty2-Year Warranty, 1-Year or 1,000h Lamp WarrantyStandard AccessoriesAC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation KitOptional AccessoriesReplacement Lamp, Remote w/ Laser Pointer	•	
Horizontal Frequency2D: 15,30 – 91.4kHz/3D: 101.6kHzVertical Scan Rate24 - 30Hz, 47 – 120HzSpeakers2W (Mono)3D ReadyYes (via DLP Link)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)Projection MethodTable Top, Ceiling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (W x D x H)274.6x 212 x 100mmWeight2.3kgNoise Level35dB/32dB (Normal/Eco Mode)Power SupplyAC 100-240V, 50/ 60HzPower Consumption240W (Normal Mode), 200W (Eco Mode)Varranty2-Year Warranty, 1-Year or 1,000h Lamp WarrantyStandard AccessoriesAC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation KitOptional AccessoriesReplacement Lamp, Remote w/ Laser Pointer		
Vertical Scan Rate24 - 30Hz, 47 - 120HzSpeakers2W (Mono)3D ReadyYes (via DLP Link)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, MiniUSB (Service)Projection MethodTable Top, Ceiling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (W x D x H)274.6x 212 x 100mmWeight2.3kgNoise Level35dB/32dB (Normal/Eco Mode)Power SupplyAC 100-240V, 50/ 60HzPower Consumption240W (Normal Mode), 200W (Eco Mode)Vo.5W (Standby Mode)Warranty2-Year Warranty, 1-Year or 1,000h Lamp WarrantyStandard AccessoriesAC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation KitOptional AccessoriesReplacement Lamp, Remote w/ Laser Pointer		
Speakers2W (Mono)3D ReadyYes (via DLP Link)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, MiniUSB (Service)Projection MethodTable Top, Ceiling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (W x D x H)274.6x 212 x 100mmWeight2.3kgNoise Level35dB/32dB (Normal/Eco Mode)Power SupplyAC 100-240V, 50/ 60HzPower Consumption240W (Normal Mode), 200W (Eco Mode)Varranty2-Year Warranty, 1-Year or 1,000h Lamp WarrantyStandard AccessoriesAC Power Cord, VGA Cable, Remote Control W/Batteries, Documentation KitOptional AccessoriesReplacement Lamp, Remote w/ Laser Pointer		·
3D Ready Yes (via DLP Link) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, MiniUSB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) CONTROL MODE) Warranty Standard Accessories Replacement Lamp, Remote w/ Laser Pointer		
Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (MiniJack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	•	, ,
1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) CONDON Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer		· '
M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) CONTINIAN OF TOTAL O	riaco companionic,	, , , , , , , , , , , , , , , , , , , ,
I/O Connection Ports VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) contine-color: 100-240V (Normal Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer		
Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) - 0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	I/O Connection Ports	
Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	-	Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-
Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (W x D x H) 274.6x 212 x 100mm Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer		USB (Service)
Dimensions (W x D x H) Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Projection Method	Table Top, Ceiling Mount (Front or Rear)
Weight 2.3kg Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) Vo.5W (Standby Mode) 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Security Solutions	Kensington® Security Slot, Keypad Lock
Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Dimensions (W x D x H)	274.6x 212 x 100mm
Power Supply AC 100-240V, 50/ 60Hz Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Weight	2.3kg
Power Consumption 240W (Normal Mode), 200W (Eco Mode) <0.5W (Standby Mode) 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Noise Level	35dB/32dB (Normal/Eco Mode)
<0.5W (Standby Mode) Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Power Supply	AC 100-240V, 50/ 60Hz
Warranty 2-Year Warranty, 1-Year or 1,000h Lamp Warranty Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Power Consumption	240W (Normal Mode), 200W (Eco Mode)
Standard Accessories AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer		<0.5W (Standby Mode)
w/Batteries, Documentation Kit Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Warranty	2-Year Warranty, 1-Year or 1,000h Lamp Warranty
Optional Accessories Replacement Lamp, Remote w/ Laser Pointer	Standard Accessories	AC Power Cord, VGA Cable, Remote Control
		w/Batteries, Documentation Kit
UPC 814964 338990	Optional Accessories	Replacement Lamp, Remote w/ Laser Pointer
	UPC	814964 338990





