



Versatile Projector

The Vivitek D865W delivers exceptional digital images with a high degree of vibrancy due to 4,000 ANSI lumens of brightness and a contrast ratio of 5,000:1. Featuring native WXGA resolution the D865W is designed for a wide variety of applications. Light weight at just over 3 kg, the D865W allow for easy transportation between different conference rooms or external meetings. For easy installation, this device offers top-loading as well as a sliding cover for quick lamp replacement. The lamp life is up to 5000 hours in Eco mode, resulting in an attractive cost of ownership.

Furthermore, the D865W has a sealed optical engine minimizing the impact of dust and smoke.

The D865W projector features a broad assortment of connectivity options to a variety of multimedia devices.

Features

- Native WXGA (1280 x 800) resolution with display up to UXGA(1600 x 1200)
- High Brightness of 4,000 ANSI lumens and high 5,000:1 Contrast ratio ensuring a crisp and sharp image
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, DisplayPort)
- Direct 3D via HDMI port
- Top-loading, sliding cover for quick and easy lamp replacement
- Built-in 10W audio speaker
- Sealed optical engine, minimizing the impact of dust and smoke
- Security solutions include: Kensington® security slot, security bar, keypad lock

Specifications	
Brightness	4000 ANSI Lumen
Native Resolution	WXGA (1280 x 800)
Max. Resolution	Up to UXGA (1600 x 1200) @60Hz
Contrast Ratio	5,000:1
Lamp Life and Type	3,500/5,000 Hours (Normal/Eco Mode), 240W / 190W
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	1.54 - 1.71:1
Image Size (Diagonal)	25.6" to 308"
Projection Distance	1.0 to 10.0 m
Projection Lens	F=2.52~2.72, f = 21.8~24mm
Zoom Ratio	1.1x
Aspect Ratio	16:10 Native, 4:3, 16:9 compatible
Offset (full image height)	114%
Keystone Correction	±40° Vertical
Speaker	10 Watt
Projection Method	Table Top or Ceiling Mount (Front or Rear)
3D compatibility	Yes, Direct 3D
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service)
Security	Kensington® Lock Port
Weight	3.15 Kg
Dimensions (W x D x H)	285 x 261 x 122 mm
Noise Level	35dB/32dB (Normal/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal/Eco Mode) <0.5W (Standby Mode)
Warranty	Standard Warranty: 3 years projector / 1 year on lamp or 1000 hours .Education Warranty: 5 years projector / 3 years on lamp or 2000 hours whichever comes first
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote and Carrying Case
UPC	814964 335951

