



## Versatile Projector

The Vivitek D867 delivers exceptional digital images with a high degree of vibrancy due to 4,000 ANSI lumens of brightness and a contrast ratio of 5,000:1. Featuring native XGA resolution the D867 is designed for a wide variety of applications. Light weight at just over 3 kg, the D867 allows for easy transportation between different conference rooms or external meetings.

For easy installation, this device offers top-loading as well as a sliding cover for quick lamp replacement. The lamp life is up to 5000 hours in Eco mode, resulting in an attractive cost of ownership. The D867 features a broad assortment of connectivity options to fully enjoy multimedia applications of any kind.

## Features

- Native XGA (1024 x 768) resolution with display up to UXGA(1600 x 1200)
- High Brightness of 4,000 ANSI lumens and high 5,000:1 Contrast ratio ensuring a crisp and sharp image
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, DisplayPort)
- Top-loading, sliding cover for quick and easy lamp replacement
- Built-in 10W audio speaker
- Sealed optical engine, minimizing the impact of dust and smoke
- Security solutions include: Kensington® security slot, security bar, keypad lock

| Specifications             |  |
|----------------------------|--|
| Brightness                 | 4000 ANSI Lumen  |
| Native Resolution          | XGA (1024 x 768)   |
| Max. Resolution            | Up to UXGA (1600 x 1200) @60Hz   |
| Contrast Ratio             | 5,000:1  |
| Lamp Life and Type         | 3,000/4,000 Hours (Normal/Eco Mode), 280W/245W   |
| Display Type               | Single 0.55" DLP® Technology by Texas Instruments  |
| Throw Ratio                | 1.6 to 1.92:1 (Distance/Width)   |
| Image Size (Diagonal)      | 25.6" to 308"  |
| Projection Distance        | 1.0 to 10.0 m  |
| Projection Lens            | F=2.50~2.72, f = 17.81~22.35mm   |
| Zoom Ratio                 | 1.2x   |
| Aspect Ratio               | 4:3 Native, 16:10 & 16:9 Compatible  |
| Offset (full image height) | 114%   |
| Keystone Correction        | ±40° Vertical  |
| Speaker                    | 10 Watt  |
| Projection Method          | Table Top or Ceiling Mount (Front or Rear)   |
| Video Compatibility        | SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)                                       |
| I/O Connection Ports       | VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) |
| Security                   | Kensington® Lock Port  |
| Weight                     | 3.15 Kg  |
| Dimensions (W x D x H)     | 285 x 261 x 122 mm   |
| Noise Level                | 39dB/37dB (Normal/Eco Mode)  |
| Power                      | Supply: AC 100-240V, 50/60Hz<br>Consumption: 350W/300W (Normal/Eco Mode) <0.5W (Standby Mode)  |
| Warranty                   | 3 Years, 1 Year (or 1,000h) on the Lamp  |
| Standard Accessories       | AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit   |
| Optional Accessories       | Replacement Lamp, Remote and Carrying Case   |
| UPC                        | 814964 335449  |

