



The 1080p Cross-Over projector for SOHO

1080p transitions from the home to the office with the Vivitek D910HD, which delivers 3000 ANSI Lumens of brightness and a 6000:1 contrast ratio. The Vivitek D910HD displays impressive color reproduction and amazing performance with the assistance of DLP® and BrilliantColor™ technologies. A stylish projector with a built-in speaker and an assortment of connectivity options, the D910HD is the ultimate match for today's high-definition presentations.

Features

- 3000 ANSI Lumens of brightness with a 6000:1 contrast ratio
- DLP® and BrilliantColor™ technologies from Texas Instruments
- Connectivity options include: HDMI, DisplayPort, VGA-in (2x), VGA-Out, composite video, component video, S-video
- Network-ready for integration and system administration via RJ45
- Direct 3D over HDMI
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments

Specifications	
Brightness	3000 ANSI Lumens
Native Resolution	1080p (1920 x 1080)
Max. Resolution	WUXGA (1920 x 1200) @60Hz
Contrast Ratio	6000:1
Lamp Life and Type	3,500/5,000 Hours (Normal/Eco Mode), 240W/190W
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	1.58 to 1.92:1 (Distance/Width)
Image Size (Diagonal)	23.5" to 300"
Projection Distance	1.0 to 10.0 m
Projection Lens	F=2.51~2.77, f = 23.5~28.2mm
Zoom Ratio	1.2x
Aspect Ratio	16:9 Native, 4:3, 16:10 Compatible
Offset (full image height)	115%
Keystone Correction	±40° Vertical
Speaker	10 Watt
Remote Control	Fully Featured IR Remote with Laser Pointer
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service)
Security	Kensington® Lock Port, Security Bar
Weight	3.15Kg
Dimensions (W x D x H)	285 x 261 x 122 mm
Noise Level	35dB/32dB (Normal/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode)
Warranty	3 Years, 1 Year (or 1,000h) on the Lamp
Education Warranty	5-Year Warranty, 3-Year (or 2,000 hours)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	

