

## DH2661Z PORTABLE PROJECTORS





# Versatile Portable Projector with High Brightness



### **FEATURES**

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 4000 ANSI lumens of brightness and 30,000:1 contrast ratio for clear, crisp and bright presentations
- 1080p (1920 x 1080) native resolution scalable up to a maximum 4K UHD (3840 x 2160) resolution
- 4K compatible in 1080p resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Auto H/V keystone geometric and 4-corner adjustment
- · Diverse connectivity, HDMI 2.0, USB-A power
- Compact and lightweight at 4.8kg for easy portability
- 3D ready and support various forms
- A long life up to 30,000 hrs. (Eco Mode) for low Total Cost of Ownership (TCO)
- Audio ready with built-in 10 watt audio speaker, audio-in and audio-out ports
- Smart Control: quick cooling, instant restart, auto power off, reminder message, Security settings, 0.5W in standby mode and more...
- · Environmentally friendly design and compliance







#### From meeting room to presentations anywhere on the road

and BrilliantColor™ technologies, delivering striking, vibrant images in a widescreen format. It provides an array of connectivity options, including two HDMI v2.0 ports, and boasts a brightness level of 4,000 ANSI Lumens with a remarkable 30,000:1 contrast ratio. Its lightweight and compact design facilitates effortless installation that will fit any budget.



#### **DH2661Z SPECIFICATIONS**

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	4000 ANSI Lumens
	Native Resolution	1080p (1920 x 1080)
	Max. Supported Resolution	4K UHD (3840 x 2160)
	Contrast Ratio	30,000:1
	Automatic Keystone Correction	Automatic Keystone Correction
	Native Aspect Ratio	16:9
	Keystone Correction	Horizontal ±30°, Vertical ±30°/ 4-Corner
Optical	Throw Ratio	1.475-1.753
	Image Size (Diagonal)	40" - 300"
	Projection Distance	1.32 - 9.9m
	Projection Lens	F = 2.5 - 2.66, f = 22 - 25.42mm
	Zoom Ratio	1.2x
	Offset	107% ±5%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Compatibility	Video	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x1), HDMI Number of Ports 2.0 (x2), Audio-In (RCA), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RJ45, RS-232, USB A (2.0 (Power 5V/1.5A)), USB miniB (Service)
General	Lamp Life and Type	20,000 / 30,000 hours (Normal / Eco)
	Speakers	10W (Mono)
	Dimensions (W x D x H)	353 x 290 x 144mm
	Weight	4.8 kg
	Noise Level	33dB/31dB (Normal/Eco Mode)
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Normal Mode), 180W (Eco Mode), <0.5W (Standby)
	Warranty	Laser Phosphor Warranty: 3-Year warranty on projector/ 3-year or 10000h or the Laser Phosphor illumination source. (Whichever comes first)
	Standard Accessories	VGA Cable, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Remote Control P/N (XX5040005400)
	UPC Code	813097025869