



Large Venue Presentation Solution for Demanding Multimedia Applications

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 6,500 ANSI lumens of brightness with dual-lamp system
- WUXGA resolution for clear and crisp image
- HDBaseT for robustness with long signal transmission
- Installation flexibility is ensured with 8 optional lenses from 0.38:1 to 5.31-8.26:1 throw ratio range
- Motorized and wide lens shift range allows easy placement of the projector without distorting the image
- Image adjustment is made easy with 4-corner and keystone corrections
- Easy projector monitor and control over network



Professional projector for WUXGA high definition presentations

The Vivitek DU6771 is designed for large meeting room where brightness and installation flexibility is the key consideration. Featuring dual-lamp technology, interchangeable lenses and advanced display technologies the DU6771 delivers bright, superb digital images with full color saturation. Intended for the heavy duty applications it can operate 24/7, delivering high brightness of 6500 ANSI Lumens. The model features a high contrast ratio of 3000:1 for deep blacks and rich colours. The DU6771 is unmatched in performance and functionalities.



DU6771

SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	6500
	Native Resolution	WUXGA (1920 x 1200)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	3,000:1
	Keystone Correction	Vertical +/- 30°, Horizontal +/- 30°
	Optical	Throw Ratio
Zoom Ratio		Motorized Zoom & Focus
Lens Shift (Based on Full Image Height)		Motorized Lens Shift
Image Size (Diagonal)		depending on lens selection
Focus		Motorized Zoom & Focus
Projection Distance		depending on lens selection
Projection Lens		8 optional lenses from 0.38:1 to 5.31-8.26:1 throw ratio range
Offset (Based on Full Image Height)		Motorized Lens Shift
Features	Features	3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI v.1.4a (2), DVI-D, Component (5 BNC) (RGBHV) , RJ45 (1: HDBaseT/LAN), RS-232, 3D-Sync (x2: In and Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote)
General	Dimensions (W x D x H)	510 x 470 x 210 mm
	Weight	18
	Power	Supply: AC 100-240V, 50/60Hz. Consumption: 572W (Eco Mode), 697W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	4,500 / 5,000 Hours (Norma / Eco Mode), 300W x 2
	Noise Level	35dB/30dB (Normal/Eco Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Warranty Card (by region), Remote Controller (with battery), AC Power Cord, Remote Control Cable
	Optional Accessories	Spare Lamp P/N (3797865400-SVK), Remote Control P/N (5041848301)
	Warranty	Large Venue Warranty: 5 years projector / 1 year on lamp or 1.000 hours whichever comes first
	UPC Code	DU6771-BK: 813097022523 DU6771-WH: 813097022509

OPTIONAL LENSES

Lens Name	Standard Lens	Wide Fix	Ultra Wide Zoom	Wide Zoom	Semi Long Zoom	Long Zoom 1	Long Zoom 2	Ultra Short Throw
Aspect Ratio	16:10	16:10	16:10	16:10	16:10	16:10	16:10	16:10
Throw Ratio	1.73-2.27:1	0.76:1	0.75-0.93:1	1.25-1.79:1	2.22-3.67:1	3.58-5.38:1	5.31-8.26:1	0.38:1
Projection Distance	1.45-24.85	0.64-8.50	0.62-10.36	1.05-19.59	1.87-40.33	3.01-59.02	4.42-91.54	0.85-2.74
Image Size	40-500	40-500	40-500	40-500	40-500	40-500	40-500	100-350
Zoom	-	-	-	-	-	-	-	-
F Number	1.7-1.9	1.85	1.96 - 2.3	1.85-2.5	1.86-2.48	1.85-2.41	1.85-2.48	2.0
Focal Length	26 - 34 mm	11.6 mm	11.3 - 14.1 mm	18.7 - 26.5 mm	32.9 - 54.2 mm	52.8 - 79.1 mm	78.5 - 121.9 mm	5.64 mm
Part Number	3797744200-SVK (D88-ST001)	3797745100-SVK (D88-WF18501)	3797804200-SVK (D88-UWZ01)	3797745200-SVK (D88-WZ01)	3797745000-SVK (D88-SMLZ01)	3797745400-SVK (D88-LOZ101)	3797744900-SVK (D88-LOZ201)	3797866500-SVK (D88-UST01B)

