



LV-SERIES  
DLP & LCD PROJECTORS

PORTABLE FIXED LENS DLP PROJECTORS

# LV-HD420 LV-X420



PROJECTORS.USA.CANON.COM

MARKETS/APPLICATIONS  
RECOMMENDED FOR:

- K-12 Education
- Higher Education
- Corporate
- Small Business
- Retail Display



**FULL HD**  
1920x1080

HDMI™ \*MHL

## HIGH-BRIGHTNESS AND CONVENIENCE.

The LV-HD420 and LV-X420 DLP Projectors are compact models that offer high-brightness with 4200 lumens, and a high contrast ratio. Resolutions available include 1080p and XGA to suit a variety of user requirements. Impressive image quality adjustment features as well as the BrilliantColor™ system, and with 6-color wheel, ensure realistic and rich colors with enhanced brightness in business presentation and classroom environments. Inputs include dual HDMI Inputs and MHL.

### KEY FEATURES

- Resolution
  - LV-HD420: 1080P (1920 x 1080)
  - LV-X420: XGA (1024 x 768)
- Contrast Ratio:
  - LV-HD420: up to 8,000:1
  - LV-X420: up to 10,000:1
- Throw Ratio:
  - LV-HD420: 1.83:1 - 2.75:1 \*1
  - LV-X420: 1.39:1 - 2.09:1 \*1
- 4200 Lumens
- DLP Technology with BrilliantColor™ System
- HDMI (x2), MHL
- Filter Free Design Simplifies Maintenance
- 3D Ready
- Network Management
- Compact
- 10W Built-in Speaker

### 4200 Lumens



With a bright 4200 lumens and easy-to-transport design, the LV-HD420 and LV-X420 projectors provide exceptional flexibility, quality and value.

### Full HD - 1080p



The LV-HD420 features Full HD 1080p for true HDTV video quality and sharpness. The LV-X420 features XGA 1024x768 resolution which is well suited to a variety of content.

\*1: Calculated at 100" diagonal

## SPECIFICATIONS

PROJECTION SYSTEM	
Imaging Device	DMD x1
Aspect Ratio	LV-HD420: 16:9 LV-X420: 4:3
Native Resolution	LV-HD420: 1080P (1920 x 1080) LV-X420: XGA (1024x768)
Brightness	4200/3360 lm <sup>*1</sup>
Uniformity	80%
Contrast Ratio	LV-HD420: 8,000:1 <sup>*2</sup> LV-X420: 10,000:1 <sup>*2</sup>
Digital Keystone	V: ±30°, H: ±30°
Electric Zoom	2x Maximum (1.8x When Overscan Display)

OPTICS	
F Number, Focal Length	F2.42 - F2.97, f=20.7 - 31.1mm
Zoom	1.5x
Focus	Manual
Image Size W	LV-HD420: 40 - 320" LV-X420: 40 - 260"
Image Size T	LV-HD420: 30 - 210" LV-X420: 30 - 170"
Projector Distance	3.9 - 32.8 ft.
Throw Ratio	LV-HD420: 1.83:1 - 2.75:1 <sup>*4</sup> LV-X420: 1.39:1 - 2.09:1 <sup>*4</sup>
Lens Shift	LV-HD420: 65%, Fixed LV-X420: 64%, Fixed


IMAGE ADJUSTMENTS	
Image Modes	Presentation / Standard / sRGB / Movie/Cinema / User 1 / User 2
Color Adjustment	Color Temperature, Color Balance, Color Tint
Screen Color Correction	Pale Yellow, Pink, Pale Green, Blue, Blackboard
Mounting	Front Table, Rear Table, Front Ceiling, Rear Ceiling
Adjustable Feet	Front : 1, Rear 1

IMAGE SIGNALS	
Scanning Frequency	V: 24 Hz - 120 Hz, H: 15.625 kHz - 101.6 kHz
Analog PC Input	WUXGA / WSXGA+ / UXGA / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA / MAC
Digital PC Input	WUXGA / WSXGA+ / UXGA / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
Component Video Input	1080p / 1080i / 720p / 576p / 480p / 576i / 480i
Digital Video Input	1080p / 1080i / 720p / 576p / 480p
MHL Input	1080p / 1080i / 720p / 576p / 480p / 576i / 480i
Video Input/S-video Input	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N

## DIMENSIONS



## CONNECTABILITY



\*1: Lamp mode is Normal/Eco. Brightness in Eco mode is only a calculated value, and is not guaranteed as specification. \*2: Full white, full black, lamp level changes by following a brightness characteristic of an image. \*3: "Standby Power" function is set to Network/RS-232. \*4: Calculated at 100° (diagonal). \*5: This time guarantees a 50% survival rate and a 50% brightness-maintenance rate. This value does not guarantee the operating life of lamp. \*6: When utilizing an MHL device, the wireless remote control does not operate.

© 2017 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Products not shown to scale. Certain images and effects are simulated. Canon and REALiS are registered trademarks of Canon Inc. in the United States and may also be trademarks or registered trademarks in other countries. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.

LV-HD420 DLP Projector	ITEM CODE: 1905C002	UPC CODE: 13803289220
LV-X420 DLP Projector	ITEM CODE: 1906C002	UPC CODE: 13803289237

TERMINALS	
Mini Dsub15	Analog PC / Component Video Input (x2), Analog PC / Component Video Output (x1)
HDMI	Digital PC / Digital Video Input
HDMI/MHL	Digital PC / Digital Video / MHL Input <sup>*6</sup>
Mini DIN4	S-video Input
RCA x3	Video Input / Audio-L / Audio-R
RJ-45	Network Connection (100BASE-TX / 10BASE-T)
Dsub9 (Control)	RS-232C
USB Type A	Power Supply Terminal (1.5A)
USB Mini B	Service Port
Mini Jack	Audio Input (x1), Audio Output (x1)
Mini Jack	12V Output (Trigger for screen operation)

REMOTE CONTROL	
Wireless Remote	IR

BUILT-IN SOUND	
Internal Amplifier	10W, Monaural

LAMP	
Type	Super-High Pressure Lamp
Life	2500H/3000H (Lamp Mode: Normal/Eco) <sup>5</sup>
Lamp Power	310/245W <sup>*1</sup>

RATINGS	
Fan Noise	40/36 dB <sup>*1</sup>
Power Consumption	410/320W <sup>*1</sup>
Standby Power Consumption	2.0/0.5W <sup>*3</sup>
Power Voltage	AC100 - 240V : 50/60Hz
Operating Temperature	41°F - 104°F (RH: 10 - 85%) (No Condensation)
Dimensions (W x D x H)	W: 12.3" x D: 9" x H: 4.4"
Weight	7.5 lbs.

## WHAT'S IN THE BOX

- Projector
- Lens Cap
- Power Cord
- Computer Cable (Mini Dsub15-Mini Dsub15)
- Projector Remote Control LV-RC11 (Includes CR2025 battery)
- Quick Start Guide (Book)
- User's Manual (CD-ROM)
- Warranty Card

## ACCESSORIES/REPLACEMENT PARTS

ITEM	ITEM CODE
Remote Control LV-RC11	2137C001
Carrying Case LV-SC02	1468C001
Replacement Lamp LV-LP42	1907C001