

CHRISTIE CAPTIVA DWU500S

Boardrooms | Classrooms | Conference rooms
Huddle spaces | Museums | Retail

Maximize your space, captivate your audience

Captivate audiences, inspire creativity, and encourage collaboration with the Christie® Captiva DWU500S 1DLP® ultra short throw laser projector.

Maximize your space without sacrificing visual impact with one of the shortest throw distances available. Easily display WUXGA resolution images up to 12.5' (3.8m) diagonal in landscape or portrait orientations.

With four-corner geometry adjustment, the DWU500S allows you to present flawless images every time, whether you're in the classroom, conference room, or retail environment.

The DWU500S provides 20,000 hours of low-cost and reliable operation, a suite of easy-to-use features, multiple mounting options, and instant on/off, letting you focus on what's important—the content.



CHRISTIE®

Technical specifications

Christie Captiva DWU500S 171-037101-01, 171-038102-01

Image	brightness (lumens)	<ul style="list-style-type: none"> • 4500 ANSI lumens • 5000 ISO lumens
	contrast	<ul style="list-style-type: none"> • 1800:1 Full on/off
Display technology	type	<ul style="list-style-type: none"> • 1-chip 0.67" DMD
	native resolution	<ul style="list-style-type: none"> • 1920 x 1200 (2,304,000 pixels) 16:10
	image size (diagonal)	<ul style="list-style-type: none"> • 130-150"
Illumination	type	<ul style="list-style-type: none"> • Solid-state laser
	typical lifetime	<ul style="list-style-type: none"> • 20,000 hrs
Signal inputs	standard	<ul style="list-style-type: none"> • HDMI x 2 • VGA x 1 • VGA audio in (3.5mm phone jack) • Microphone input • USB A - for power out only (5V/1.5A)
	max input pixel rate	<ul style="list-style-type: none"> • 1600 x 1200 @ 60Hz (162 MHz) • 1920 x 1200 @ 60Hz reduced blanking (154 MHz)
	3D	<ul style="list-style-type: none"> • Frame packed/side-by-side/top and bottom 3D (HDMI 1.4a) • Frame sequential DLP link 3D (VGA/HDMI) • Frame sequential DLP link 3D (1024 x 768 @120Hz / 1280 x 720 @120Hz)
	pixel clock	<ul style="list-style-type: none"> • 162 MHz
Signal outputs		<ul style="list-style-type: none"> • VGA monitor out • 10W speaker • Audio output (3.5mm phone jack)
Control and networking		<ul style="list-style-type: none"> • RS-232 in • Ethernet (100BaseT) RJ45 • Built-in keypad • Compatible with Crestron RoomView, AMX, PJ Link
Accessories	standard	<ul style="list-style-type: none"> • IR remote • AC Line cord for projector head
	optional	<ul style="list-style-type: none"> • Wall mount
Lens	adjustment	<ul style="list-style-type: none"> • Focus adjustment
	lens	<ul style="list-style-type: none"> • 0:25:1 ultra short throw lens
	offsets	<ul style="list-style-type: none"> • Fixed offset based on image size
Power requirements	operating voltage	<ul style="list-style-type: none"> • 100-240 VAC @ 50/60Hz
	power consumption	<ul style="list-style-type: none"> • 350W +/-15% @110V max • 250W +/-15% @110V eco mode
	operating current	<ul style="list-style-type: none"> • 3.2A +/-15% @110V
	dissipation	<ul style="list-style-type: none"> • 1373 BTU/hr max • 981 BTU/hr eco mode
Audible noise		<ul style="list-style-type: none"> • Standard mode: 36dBA • Eco mode: 30dBA
Physical	size	<ul style="list-style-type: none"> • (LxWxH) 12.5 x 15.08 x 3.46" (318 x 383 x 88mm) w/o feet
	weight	<ul style="list-style-type: none"> • 12.79lbs (5.8kg)
	shipping size	<ul style="list-style-type: none"> • (LxWxH) 20.4 x 16.5 x 12.9" (518 x 420 x 328 mm)
	shipping weight	<ul style="list-style-type: none"> • 17.2lbs (7.8 kg)
Operating environment	temperature	<ul style="list-style-type: none"> • Temp: 40-104°F (5-40°C)
	humidity	<ul style="list-style-type: none"> • Humidity: 10-85% non-condensing
Regulatory		<ul style="list-style-type: none"> • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • UL/CSA/IEC 60950-1 • FCC Class A • CE • CCC • CU • BIS
Warranty		<ul style="list-style-type: none"> • 3 years on the projector • 3 years or 20,000 hours on the illumination system¹ • Contact an authorized Christie representative for full details of our limited warranty

¹ Reference the Christie Standard Limited Warranty document for details.

Christie support and services

All Christie products are backed by industry-leading warranties, and renowned service and support. We ensure our customers are well-supported with training, service, and technical knowledge through our extensive distribution and support network.

For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP Logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD3810-Christie-Captiva-DWU500S-Datasheet-Aug-23-EN

