

# W515T

# A Powerful Performer

- Geometry correction 4 corner
- x1.8 Zoom with vertical and horizontal lens shift
- HDBaseT connectivity
- 6000 lumens WXGA DLP projector



























# W515T

Built for demanding professional applications, the powerful high-specification W515T projector boasts a brightness of 6,000 lumens and features multiple digital connection options, with two HDMI inputs, DisplayPort and HDBaseT. For more complex installations, this projector is equipped with a large zoom range, lens shift and a built-in geometric adjustment feature - ideal for image stacking, uneven walls or where a projector placement is awkward and needs to be installed at an angle.

# **High Contrast**

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.





#### Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.



#### Integrated speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers.

# **Energy saving**

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance.

# Auto power off

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto power off" feature automatically turns off the projector after a set period of time.

#### **Eco AV mute**

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.





#### **PureShift**

Simplify installation with PureShift, which provides a wide range of projector placement possibilities.

# Four-corner adjustment

Individually warp each corner of the image to create a perfectly square image. Ideal for image stacking, uneven walls or where projector placement is awkward and needs to be installed at an angle.

#### **Brightness matching**

The brightness of a projector will vary throughout its life. To correctly match multiple units, the projector has set lamp power modes (stepped lamp dimming) to help match the brightness of both projectors.





#### MHL

Turn your projector into a smart display by connecting your smartphone or tablet with a single cable using MHL, enabling you to view presentations and documents, stream videos and share photos on the big screen.



#### Large zoom range

A large zoom range enables multiple placement possibilities at a variety of distances from the projection screen. An advantage to this is that expensive interchangeable lens projectors can be substituted with a more cost effective solution whilst still retaining a diverse choice of positioning options.

# Long lamp life

Reduce the number of lamp changes with long lamp life

# **Networking and control**

Featuring a wide range of options you can remotely control and monitor the projector.

#### **RS232**

Optoma projector's come with an extensive set of RS232 commands making it simple and easy to manage using any control system.

#### **AMX Compatibility**

Dynamic discovery protocol is incorporated into the projector allowing for easy installation with AMX control systems.

#### **LAN Control**

- Using the compatible RoomView® software you can power on/off, monitor, manage and control up to 250 projectors at the same time from any computer.
- Schedule the projectors to power on/off.
- Control and alter the projector settings using the simple web browser.
- Emergency text broadcast capabilities for urgent or important announcements.
- Automatically receive email updates for lamp maintenance.





#### **Colour Guarantee**

We are so confident that the image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.





# **Amazing Colour**

Give powerful presentations and educational lessons with stunning colours. Optoma projectors provide you with reliable colour performance suitable for any content and environment. From accurate sRGB colours for true life like images to vibrant punchy presentations. We have a display mode to specific meet your needs.





# **Quick resume**

This feature allows the projector to be instantly powered on again, if it

is accidentally switched off.



# **USB** power

Use the USB-Power to power an HDMI dongle, such as Google Chromecast or the Optoma WHD200 wireless HDMI device.

# Image stacking

Double your image brightness without significantly increasing your installation cost; with warp adjustment, you can achieve any brightness you want. Image stacking permits flexible installations and greater redundancy; an image can be displayed without interruption while swapping lamps. Alternatively, images can be realigned to be perfectly square if aligned beyond the lens shift range.

#### Wired remote

The wired remote connection allows all aspects of the projector to be individually controlled without requiring a line-of-sight to the projector; invaluable when using multiple units during live events.

# **HDBaseT**

Simplify installation by transmitting uncompressed HD video, audio, Ethernet and control commands using a standard LAN cable of up to 100m.

# **W515T Specification**

Native Resolution         WXX6A 1280 x 800           Brightness* (Bright Mode)         6000 ANSI Lumens           Contrast         10,000-1           Lamp Life* EcoRinght         5000/30000 (Ins)           Throw Ratio         1,26-2,288 1, Offset: 105%-125%           Zonn Sypie         1.8x Manual           Lorn Sypie         1.8x Manual           Violonamic Connectors         1.x HDBsset (RU-45) 2x HDMI (14-8 30 support) + MHL. DisplayPort, 2 x VGA (YPPP/RCB), 8-Video, Composite, 3 x Audio in (RCA/3 5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V frigger, 30-Sync, Wired remote           Speaker (Watts)         20           Keystone Correction         ± 30" Vertract ± 30" Horizontal           Weight (Kg)         5.9           Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:943 Compatible           Offset         105%           Projection Distance         1.3m to 8.2m	Display Technology	Single 0.65" WXGA DLP® Technology by Texas Instruments
Contrast         10,000:1           Lamp Life <sup>2</sup> Eco/Bright         5000/3000 (hrs)           Trow Ratio         1,28-2,286.1, Offset: 105%-125%           Zoom Type         1,8x Manual           Lens Shift         Vertical: 420 Horizontal: 4/-10% (constraints apply see user manual for details)           I/C Connectors         1 x HDBase*(RL-145); 2x HDMI (1.4a; 3D support) + MHL, DisplayPort, 2x VGA (YPPbr/RGB), S-Video, Composite, 3 x Audio (RCA03, Smm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, R.H45, 12V trigger, 3D-Spre, Wired remote           Speaker (Watts)         20           Keystone Correction         4 30° Vertical: ± 30° Horizontal           Weight (Kg)         5.9           Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:94/3 Compatible           Offset         105%           Projection Distance         1.3m to 8.2m           Projection Distance         1.3m to 8.2m           Projection Distance         1.2m to 8.2m           Projection Distance		0, ,
Contrast         10,000:1           Lamp Life <sup>2</sup> Eco/Bright         5000/3000 (hrs)           Trow Ratio         1,28-2,286.1, Offset: 105%-125%           Zoom Type         1,8x Manual           Lens Shift         Vertical: 420 Horizontal: 4/-10% (constraints apply see user manual for details)           I/C Connectors         1 x HDBase*(RL-145); 2x HDMI (1.4a; 3D support) + MHL, DisplayPort, 2x VGA (YPPbr/RGB), S-Video, Composite, 3 x Audio (RCA03, Smm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, R.H45, 12V trigger, 3D-Spre, Wired remote           Speaker (Watts)         20           Keystone Correction         4 30° Vertical: ± 30° Horizontal           Weight (Kg)         5.9           Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:94/3 Compatible           Offset         105%           Projection Distance         1.3m to 8.2m           Projection Distance         1.3m to 8.2m           Projection Distance         1.2m to 8.2m           Projection Distance	Brightness <sup>1</sup> (Bright Mode)	6000 ANSI Lumens
Throw Ratio         1.28-2.288.1, Offset: 105%-125%           Zoom Type         1.8x Manual           Lens Shift         Vertical: +20 Horizontal: +4-10% (constraints apply see user manual for details)           I/O Connectors         1 x HDBase*(FRL-46) z x HDMI (1 4s 30 support) + MHL. DisplayPort, 2 x VGA (YPDP/IRGB), S-Video, Composite, 3 x Audio in (RCAx3.5mm), Mic In., Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, R.I45, 12V trigger, 3D-Sync, Wred remote           Speaker (Watts)         20           Keystone Correction         2 30" Vertical ± 30" Horizontal           Weight (kg)         5.9           Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:34:3 Compatible           Offset         105%           Projection Distance         1.3m to 8.2m           Projection Distance         1.3m to 8.2m           Projection Distance         1.3m to 8.2m           Video Compatibility         B0%           Video Compatibility         B0%           Video Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p           3D Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p           3D Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p           3D Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p		10,000:1
Throw Ratio         1.28-2.288.1, Offset: 105%-125%           Zoom Type         1.8x Manual           Lens Shift         Vertical: +20 Horizontal: +4-10% (constraints apply see user manual for details)           I/O Connectors         1 x HDBase*(FRL-46) z x HDMI (1 4s 30 support) + MHL. DisplayPort, 2 x VGA (YPDP/IRGB), S-Video, Composite, 3 x Audio in (RCAx3.5mm), Mic In., Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, R.I45, 12V trigger, 3D-Sync, Wred remote           Speaker (Watts)         20           Keystone Correction         2 30" Vertical ± 30" Horizontal           Weight (kg)         5.9           Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:34:3 Compatible           Offset         105%           Projection Distance         1.3m to 8.2m           Projection Distance         1.3m to 8.2m           Projection Distance         1.3m to 8.2m           Video Compatibility         B0%           Video Compatibility         B0%           Video Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p           3D Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p           3D Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p           3D Compatibility         PLA SECAM 578ip, NTSC 480ip, HD 720p/1080i/1080p	Lamp Life <sup>2</sup> Eco/Bright	5000/3000 (hrs)
2.00m Type		
Lens Shift		· · · · · · · · · · · · · · · · · · ·
A FIDBASET (R.J. 45) 2 x FIDMI (1 4a 3D support) + MHL, DisplayPort, 2 x VGA (YPBP/RGB), S-Video, Composite, 3 x Audio In (R.CA/3.5mm), Mic In Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, R.J.45, 12V trigger, 3D-Sync, Wired remote		
Keystone Correction         ± 30° Vertical ± 30° Horizontal           Weight (kg)         5.9           Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:94:3 Compatible           Offset         105%           Projection Screen Size         24,7°-302,7° Diagonal 16:10           Projection Lens         F12.3-3.39; f=17.63-31.36mm, 1.8x Manual Zoom           Uniformity         80%           Computer Compatibility         UXGA, SXGA+, HD, WXGA, XGA, SVGA           Video Compatibility         PAL SECAM 576i/p, NTSC 48u/p, HD 720/p1080/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Bit-ray 3D™ and 3D garnes from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080505 160, 720p50 160           Point Consumption         Side-by-Side:1080505 160, 720p50 160           Point Consumption         15.375-91.146 KHz           Vertical Scan Rate         15.375-91.146 KHz           Displayable Colours         1.07 Billion           Noise Level (Eco mode)         28           Power Supply         100-240V, 50-60Hz           Power Supply		1 x HDBaseT(RJ-45) 2 x HDMI (1.4a 3D support) + MHL, DisplayPort, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger,
Weight (kg)         5.9           Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:9/4:3 Compatible           Offset         105%           Projection Screen Size         24.7"-302.7" Diagonal 16:10           Projection Distance         1.3m to 8.2m           Projection Lens         F/2.3-3.39; Fe17.63-31.36mm, 1.8x Manual Zoom           Uniformity         80%           Computer Compatibility         UXGA, SXGA+, HD, WXGA, XSA, SVGA           Video Compatibility         PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080i50 / 60, 720p50 / 60           Horizontal Scan Rate         15.375-91.146 KHz           Vertical Scan Rate         15.375-91.146 KHz           Vertical Scan Rate         24-88 Ft 2 (120Hz for 3D feature)           Displayable Colours         1.07 Billion           Noise Level (Eco mode)         28           Power Supply         100-240V, 50-60Hz           Power Consumption	Speaker (Watts)	20
Dimensions (W x D x H) (mm)         424 x 344 x 160           Aspect Ratio         16:10 Native, 16:9/4:3 Compatible           Offset         105%           Projection Screen Size         24.7"-302.7" Diagonal 16:10           Projection Distance         1.3m to 8.2m           Projection Lens         F72.9-3.39; f=17.63-31.36mm, 1.8x Manual Zoom           Uniformity         80%           Computer Compatibility         UXGA, SXGA+, HD, WXGA, XGA, SVGA           Video Compatibility         PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080l/1080p           3D Support         Full 30 - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:108060 f 60, 720p50 / 60           Frame-pack: 108060 f 60, 720p50 / 60         Cover-Under: 1080p24, 720p50 / 60           Horizontal Scan Rate         15.375-91.146 KHz           Vertical Scan Rate         24~ 85 Hz (120Hz for 3D feature)           Displayable Colours         1.07 Billion           Noise Level (Eco mode)         28           Power Consumption         425W Bright mode, 340W Eco mode, <0.5W Standby mode           Lamp Type         <	Keystone Correction	± 30° Vertical ± 30° Horizontal
Aspect Ratio         16:10 Native, 16:9/4:3 Compatible           Offset         105%           Projection Screen Size         24,7"-302.7" Diagonal 16:10           Projection Distance         1.3m to 8.2m           Projection Lens         F/2,3~3.9; f=17.63~31.36mm, 1.8x Manual Zoom           Uniformity         80%           Computer Compatibility         UXGA, SXGA+, HD, WXGA, XGA, SVGA           Video Compatibility         PAL SECAM 576/IP, NTSC 480/IP, HD 720p/1080i/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D garnes from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080i50 / 60, 720p50 / 60           Frame-pack: 1080p24, 720p50 / 60         Power-Under: 1080p24, 720p50 / 60           Horizontal Scan Rate         15.375-91.148 KHz           Vertical Scan Rate         24-85 Hz (120Hz for 3D feature)           Displayable Colours         1.07 Billion           Noise Level (Eco mode)         28           Power Supply         100-240V, 50-60Hz           Power Consumption         425W Bright mode, 340W Eco mode, <0.5W Standby mode	Weight (kg)	5.9
Offset         105%           Projection Screen Size         24.7"-302.7" Diagonal 16:10           Projection Distance         1.3m to 8.2m           Projection Lens         F/2.3~3.39; f=17.63~31.36mm, 1.8x Manual Zoom           Uniformity         80%           Computer Compatibility         UXGA, SXGA+, HD, WXGA, XGA, SVGA           Video Compatibility         PAL SECAM 576/Ip, NTSC 480/Ip, HD 720p/1080i/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080616 / 60, 720p50 / 60           Frame-pack: 1080p24, 720p50 / 60         Frame-pack: 1080p24, 720p50 / 60           Horizontal Scan Rate         15.375~91.146 KHz           Vertical Scan Rate         24-85 Hz (120Hz for 3D feature)           Displayable Colours         1.07 Billion           Noise Level (Eco mode)         28           Power Supply         100-240V, 50-60Hz           Power Supply         100-240V, 50-60Hz           Power Supply         100-240V, 50-60Hz           Security         Kensington Lock, Password Protection <t< td=""><td>Dimensions (W x D x H) (mm)</td><td>424 x 344 x 160</td></t<>	Dimensions (W x D x H) (mm)	424 x 344 x 160
Projection Screen Size         24.7"~302.7" Diagonal 16:10           Projection Distance         1.3m to 8.2m           Projection Lens         Fi.23~3.95; f=17.63~31.36mm, 1.8x Manual Zoom           Uniformity         80%           Computer Compatibility         UXGA, SXGA+, HD, WXGA, XGA, SVGA           Video Compatibility         PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080160 / 60, 720p50 / 60           Frame-pack: 1080p24, 720p50 / 60         Cover-Under: 1080p24, 720p50 / 60           Over-Under: 1080p24, 720p50 / 60         Over-Under: 1080p24, 720p50 / 60           Vertical Scan Rate         15.375~91.146 KHz           Vertical Scan Rate         24-85 Hz (120Hz for 3D feature)           Displayable Colours         1.07 Billion           Noise Level (Eco mode)         28           Power Consumption         425W Bright mode, 340W Eco mode, <0.5W Standby mode	Aspect Ratio	16:10 Native, 16:9/4:3 Compatible
Projection Distance 1.3m to 8.2m Projection Lens Fr/2.3~3.39; f=17.63~31.36mm, 1.8x Manual Zoom Uniformity 80% Computer Compatibility UXGA, XSGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/p, NTSC 480/ip, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over	Offset	105%
Projection Lens F/2.3~3.39; f=17.63~3.136mm, 1.8x Manual Zoom Uniformity 80% Computer Compatibility UXGA, SKGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educacional or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Frame-pack: 180p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.375~91.146 KHz Vertical Scan Rate 24-485 Hz (120Hz for 3D feature) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28 Power Supply 100-240V, 50-60Hz Power Consumption 425W Bright mode, 340W Eco mode, <0.5W Standby mode Lamp Type 365W Security Kensington Lock, Password Protection Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Nireless 360' Operation Not supported	Projection Screen Size	24.7"~302.7" Diagonal 16:10
Uniformity Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.375~91.146 KHz Vertical Scan Rate 24~ 85 Hz (120Hz for 3D feature) Displayable Colours Noise Level (Eco mode) 28 Power Supply 100-240V, 50-60Hz Power Consumption 425W Bright mode, 340W Eco mode, <0.5W Standby mode Lamp Type 365W Security Kensington Lock, Password Protection Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes 360' Operation Not supported Not supported Warranty 1 Year RoHS Compliant	Projection Distance	1.3m to 8.2m
Computer Compatibility         UXGA, SXGA+, HD, WXGA, XGA, SVGA           Video Compatibility         PAL SECAM 576½p, NTSC 480½p, HD 720p/1080i/1080p           3D Support         Full 30 - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080i50 / 60, 720p50 / 60           Frame-pack: 1080p24, 720p50 / 60           Over-Under: 1080p24, 720p50 / 60           Horizontal Scan Rate         15.375-91.46 kHz           Vertical Scan Rate         24~85 Hz (120Hz for 3D feature)           Displayable Colours         1.07 Billion           Noise Level (Eco mode)         28           Power Supply         100-240V, 50-60Hz           Power Consumption         425W Bright mode, 340W Eco mode, <0.5W Standby mode	Projection Lens	F/2.3~3.39; f=17.63~31.36mm, 1.8x Manual Zoom
Video Compatibility       PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p         3D Support       Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKV in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.         3D Compatibility       Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60         Horizontal Scan Rate       15.375-91.146 KHz         Vertical Scan Rate       24~85 Hz (120Hz for 3D feature)         Displayable Colours       1.07 Billion         Noise Level (Eco mode)       28         Power Supply       100-240V, 50-60Hz         Power Consumption       425W Bright mode, 340W Eco mode, <0.5W Standby mode	Uniformity	80%
Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 7	Computer Compatibility	UXGA, SXGA+, HD, WXGA, XGA, SVGA
with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Perical Scan Rate 15.375~91.146 KHz Vertical Scan Rate 24~85 Hz (120Hz for 3D feature) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28 Power Supply 100-240V, 50-60Hz Power Consumption 425W Bright mode, 340W Eco mode, <0.5W Standby mode Lamp Type 365W Security Kensington Lock, Password Protection Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes 360' Operation Not supported Portrait Mode Not supported Warranty 1 Year RoHS Compliant	Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p
Side-by-Side:1080j50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate  15.375~91.146 KHz Vertical Scan Rate  24~ 85 Hz (120Hz for 3D feature) Displayable Colours  1.07 Billion Noise Level (Eco mode) 28 Power Supply 100-240V, 50-60Hz Power Consumption 425W Bright mode, 340W Eco mode, <0.5W Standby mode Lamp Type 365W Security Kensington Lock, Password Protection Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes 360' Operation Not supported Warranty 1 Year RoHS Compliant	3D Support	with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D
Vertical Scan Rate       24~ 85 Hz (120Hz for 3D feature)         Displayable Colours       1.07 Billion         Noise Level (Eco mode)       28         Power Supply       100-240V, 50-60Hz         Power Consumption       425W Bright mode, 340W Eco mode, <0.5W Standby mode	3D Compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60
Displayable Colours       1.07 Billion         Noise Level (Eco mode)       28         Power Supply       100-240V, 50-60Hz         Power Consumption       425W Bright mode, 340W Eco mode, <0.5W Standby mode	Horizontal Scan Rate	15.375~91.146 KHz
Noise Level (Eco mode)       28         Power Supply       100-240V, 50-60Hz         Power Consumption       425W Bright mode, 340W Eco mode, <0.5W Standby mode	Vertical Scan Rate	24~ 85 Hz (120Hz for 3D feature)
Power Supply       100-240V, 50-60Hz         Power Consumption       425W Bright mode, 340W Eco mode, <0.5W Standby mode	Displayable Colours	1.07 Billion
Power Consumption 425W Bright mode, 340W Eco mode, <0.5W Standby mode  Lamp Type 365W  Security Kensington Lock, Password Protection  Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual  Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount  Optional Wireless Yes  360' Operation Not supported  Portrait Mode Not supported  Warranty 1 Year  RoHS Compliant	Noise Level (Eco mode)	28
Lamp Type     365W       Security     Kensington Lock, Password Protection       Standard Accessories     AC power cord, VGA cable, remote control, battery, quick start card, CD user manual       Optional Accessories     DLP® Link™ 3D glasses, wireless, ceiling mount       Optional Wireless     Yes       360' Operation     Not supported       Portrait Mode     Not supported       Warranty     1 Year       RoHS     Compliant	Power Supply	100-240V, 50-60Hz
Security       Kensington Lock, Password Protection         Standard Accessories       AC power cord, VGA cable, remote control, battery, quick start card, CD user manual         Optional Accessories       DLP® Link™ 3D glasses, wireless, ceiling mount         Optional Wireless       Yes         360' Operation       Not supported         Portrait Mode       Not supported         Warranty       1 Year         RoHS       Compliant	Power Consumption	425W Bright mode, 340W Eco mode, <0.5W Standby mode
Standard Accessories       AC power cord, VGA cable, remote control, battery, quick start card, CD user manual         Optional Accessories       DLP® Link™ 3D glasses, wireless, ceiling mount         Optional Wireless       Yes         360' Operation       Not supported         Portrait Mode       Not supported         Warranty       1 Year         RoHS       Compliant	Lamp Type	365W
Optional Accessories     DLP® Link™ 3D glasses, wireless, ceiling mount       Optional Wireless     Yes       360' Operation     Not supported       Portrait Mode     Not supported       Warranty     1 Year       RoHS     Compliant	Security	Kensington Lock, Password Protection
Optional Wireless Yes 360' Operation Not supported Portrait Mode Not supported Warranty 1 Year ROHS Compliant	Standard Accessories	AC power cord, VGA cable, remote control, battery, quick start card, CD user manual
360' Operation         Not supported           Portrait Mode         Not supported           Warranty         1 Year           RoHS         Compliant	Optional Accessories	DLP® Link™ 3D glasses, wireless, ceiling mount
Portrait Mode Not supported Warranty 1 Year ROHS Compliant	Optional Wireless	Yes
Warranty 1 Year ROHS Compliant		Not supported
RoHS Compliant	Portrait Mode	Not supported
·	Warranty	1 Year
Features V/H Lens Shift, Crestron RoomView®, PJ-Link	RoHS	Compliant
	Features	V/H Lens Shift, Crestron RoomView®, PJ-Link



#### Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

—1—/Brightness and lamp lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. —2—/Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions. Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (a) Guarantee is voided if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other faults. (d) Over time worn lamps within all projector types will show a slight colour variance. Copyright © 2013, Optoma Europe Ltd. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Crestron®, the Crestron and RoomView® logo are registered trademarks or Crestron Electronics, Inc. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. All images of products are for representation purposes only. Whilst every care is taken to provide accurate images of our products, actual products may differ slightly. Some product images may have been digitally altered by us to add an Optoma logo to the front panel. Optoma reserves the right to amend or alter actual product or product images without notice. Some images may be simulated.

Copyright © 2017, Optoma Europe Limited. Optoma, NuForce and Nu are registered trademarks of Optoma Corporation. Optoma Europe Limited is the licensee of the registered trademarks. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. All images are for representation purposes only and may be simulated. All content on this site is protected by copyright.

**Privacy Terms and conditions** 

Registered Office: 42 Caxton Way, Watford Business Park, Watford. WD18 8QZ . Registered No. 3399395

05/02/2017 23:15